

Power Distribution Blocks

600 Volts

Specifications:

- Connector, High Conductive Aluminum, Tin Plated
- Amp Rating Based on NEC Table 310-16 Using 75° C Copper Wire
- *Wire Connector Rated 90° C
- UL Recognized File No. E62806
- CSA Certified File No. LR19766
- CE



** Openings rated for #4-14 AWG are multiple wire rated: (2) #10 CU Str, (2 to 4) #12 CU Str, and (2 to 4) #14 CU Str.

*** Openings rated for #2-14 AWG are multiple wire rated: (2) #8 CU Str, (2) #10 CU Str, (2) #12 CU Str, And (2) #14 CU Str

Catalog #	Poles	Amps	Material	Connector Configuration	Line Wire Range	Openings Per Pole	Connector Configuration	Load Wire Range	Openings Per Pole
1411403	1	60	Thermoplastic		#2-#14 AWG	1		#10-#18 AWG	2
1412403	2								
1413403	3								
1414403	4								
1411400	1	115	Thermoplastic		#2-#14 AWG	1		#10-#16 AWG	4
1412400	2								
1413400	3								
1414400	4								
1320570	Adder	175	Thermoplastic		2/0-#14 AWG	1		** #4-#14 AWG	4
1321570	1								
1322570	2								
1323570	3								
1421570	1	175	Phenolic		2/0-#14 AWG	1		** #4-#14 AWG	4
1422570	2								
1423570	3								
1320580	Adder	175	Thermoplastic		2/0-#14 AWG	1		** #4-#14 AWG	6
1321580	1								
1322580	2								
1323580	3								
1402402	2	175	Phenolic		2/0-#14 AWG	1		** #4-#14 AWG	4
1403402	3								
1402401	2	175	Phenolic		2/0-#14 AWG	1		** #4-#14 AWG	6
1403401	3								
1402404	2	310	Phenolic		350 kcmil - #6 AWG	1		#4-#14 AWG	6
1403404	3								
1331554	1	310	Thermoplastic		350 kcmil - #6 AWG	1		#2/0-#14 AWG	2
1332554	2								
1333554	3								
1441401	1	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	6
1442401	2								
1443401	3								
1431552	1	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	4
1432552	2								
1433552	3								
1431553	1	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	6
1432553	2								
1433553	3								
1441560	1	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	8
1442560	2								
1443560	3								
1331552	1	335	Thermoplastic		400 kcmil - #6 AWG	1		*** #2-#14 AWG	4
1332552	2								
1333552	3								