

# Power Distribution Blocks (Cont.)





























## 600 Volts

### Specifications:

- Connector, High Conductive Aluminum, Tin Plated
- Amp Rating Based on NEC Table 310-16 Using 75° C Copper Wire
- \*Wire Connector Rated 90° C
- UL Recognized File No. E62806
- CSA Certified File No. LR19766
- CE

\*\* Openings rated for #4-14 AWG are multiple wire rated:  
(2) #10 CU Str, (2 to 4) #12 CU Str, and (2 to 4) #14 CU Str.

\*\*\* Openings rated for #2-14 AWG are multiple wire rated:  
(2) #8 CU Str, (2) #10 CU Str, (2) #12 CU Str, And  
(2) #14 CU Str

Catalog #	Poles	Amps	Material	Connector Configuration	Line Wire Range	Openings Per Pole	Connector Configuration	Load Wire Range	Openings Per Pole	
1331598	1	510	Thermoplastic		250 kcmil - #1/0 AWG	2		2/0 -#14 AWG	4	
1332598	2									
1333598	3									
1451587	1	665	Phenolic		500 kcmil - #4 AWG	1		2/0 -#14 AWG	4	
1452587	2									
1453587	3									
1451592	1	760	Phenolic		500 kcmil - #4 AWG	2		** #4 - #14 AWG	12	
1452592	2									
1453592	3									
1451586	1	760	Phenolic		500 kcmil - #4 AWG	2		2/0 -#14 AWG	8	
1452586	2									
1453586	3									
1451411	1	840	Phenolic		600 kcmil - #2 AWG	2		3/0 - #6 AWG	4	
1452411	2									
1453411	3									
1320970	Adder	175	Thermoplastic	CU 	2/0 - #14 AWG	1		** #4- #14 AWG	4	
1321970										1
1322970										2
1323970										3
1421970	1	175	Phenolic	CU 	2/0 - #14 AWG	1		** #4- #14 AWG	4	
1422970	2									
1423970	3									
1431955	1	350	Phenolic	CU 	2/0 - #14 AWG	2		** #4- #14 AWG	6	
1432955	2									
1433955	3									
1431953	1	380	Phenolic	CU 	500 kcmil - #4 AWG	1		#2-#14 AWG	6	
1432953	2									
1433953	3									
1331955	1	350	Thermoplastic	CU * 	2/0 - #14 AWG	2		** #4 -#14 AWG	6	
1332955	2									
1333955	3									
1331953	1	380	Thermoplastic	CU * 	500 kcmil - #4 AWG	1		*** #2 -#14 AWG	6	
1332953	2									
1333953	3									
1451992	1	760	Phenolic	CU 	500 kcmil - #4 AWG	2		#2 -#14 AWG	12	
1452992	2									
1453992	3									
1451986	1	760	Phenolic	CU 	500 kcmil - #4 AWG	2		2/0-#14 AWG	8	
1452986	2									
1453986	3									
1453401	3	2280	Phenolic		500 kcmil - #4 AWG	6		2/0-#14 AWG	18	