

Double Row Terminal Blocks

400 Series

600 Volts

Specifications:

- Base, General Purpose Phenolic, 150° C
- Closed Back Design
- Screws, #10-32 Binder Head, Phil-Slot
- Terminals, Plated Brass
- 1-12 Poles
- 11/16" Centers
- Wire Range With Wire Binding Screw #10-#22 AWG – 30 Amps
- Wire Range With Sems Pressure Screw #10-#22 AWG Stranded Copper Wire Only, 30 Amps
- Will Accommodate Lugs For Wire Sizes #6-#16 AWG – 65 Amps
- The Suitability Of These Devices For Greater Currents Shall Be Determined In The End-Use Application
- UL Recognized File No. E62806
- CSA Certified File No. LR19766
- CE



Catalog #	# of poles	Dimensions	
		A	B
401	1	1.81	1.38
402	2	2.50	2.06
403	3	3.19	2.75
404	4	3.88	3.44
405	5	4.56	4.12
406	6	5.25	4.81
407	7	5.94	5.50
408	8	6.62	6.19
409	9	7.31	6.88
410	10	8.00	7.56
411	11	8.68	8.25
412	12	9.37	8.94

Hardware Options: (Hardware options may affect ratings - consult factory)

- SPSE = Sems Pressure Saddle Screw
 J603(LL 400) = Line to Line Jumper See Page 96

