



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ANDERSON POWER PRODUCTS. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ANDERSON POWER PRODUCTS IS PROHIBITED.

REV.	DESCRIPTION OF CHANGES	BY:	DATE
1	ECRN 14110 - REDRAWN	AMS	2/28/07

ITEM NO.		PART OR IDENTIFYING NO.		NOMENCLATURE OR DESCRIPTION			MATERIAL SPECIFICATION		QTY REQD		
COPYRIGHT 1999 ANDERSON POWER PRODUCTS. ALL RIGHTS RESERVED. UNAUTHORIZED REPRODUCTION HEREBY PROHIBITED.											
		DIMENSIONS ARE IN INCHES DIMENSIONS IN PARENTHESES [] ARE IN MILLIMETERS		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		ANDERSON POWER PRODUCTS					
				APPROVALS	DATE						
		TOLERANCES ARE: 2PL- ±.02 [±.5]		DRAWN	CMS	6/29/99	CATALOG NUMBER 269G2 15 AMP HIGH DETENT CONTACT FOR REEL TYPE "F" CRIMP #16-20 WIRE				
				CHECKED	DJD	6/30/99					
		MATERIALS: COPPER		RESP ENG	UFN	6/30/99					
				MFG ENG	CHB	6/30/99					
NEXT ASSY		USED ON	FINISH HOT TIN DIP		QUAL ENG	RPO	7/6/99	SIZE A	SPECIFICATION: 113967S2		REV. 1
APPLICATION		DO NOT SCALE DRAWING			SCALE NONE	CADFILES/01062			SHEET 1 OF 1		