


Wire and Cable Marking

CONTINUED



WIRE MARKING LABELS

Self-Laminating Vinyl (B-427), Repositional Vinyl Cloth (B-498), Nylon Cloth (B-499), Self-Laminating Tedlar® (B-642)

Diagram	Part Number	Labels Per Roll	Label Dimensions		Write-On Height Inch (mm) C	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:			
			Inch (mm) A	Inch (mm) B		2	7	10	2	7	10	
4 to 10 GAUGE WIRE (AWG) Based on THHN Wire - Maximum Wire Diameter - 0.260 in (6.64 mm)												
▶	PTL-28-427**	750	0.250 (6.35)	1.500 (38.10)	0.500 (12.70)	5	2	1	5	2	1	
▶	PTL-28-498	750	0.250 (6.35)	1.500 (38.10)		5	2	1	16	8	5	
▶	PTL-28-499	750	0.250 (6.35)	1.500 (38.10)		5	2	1	16	8	5	
▶	PTL-29-498	500	0.500 (12.70)	1.500 (38.10)		11	5	3	16	8	5	
▶	BPTL-29-498	5000	0.500 (12.70)	1.500 (38.10)		11	5	3	16	8	5	
▶	PTL-29-427**	500	0.500 (12.70)	1.500 (38.10)	0.500 (12.70)	11	5	3	5	2	1	
▶	PTL-29-499	500	0.500 (12.70)	1.500 (38.10)		11	5	3	16	8	5	
▶	PTL-30-427**	250	0.750 (19.05)	1.500 (38.10)	0.500 (12.70)	18	7	5	5	2	1	
▶	BPTL-30-427	2500	0.750 (19.05)	1.500 (38.10)	0.500 (12.70)	18	7	5	5	2	1	
▶	PTL-30-498	250	0.750 (19.05)	1.500 (38.10)		18	7	5	16	8	5	
▶	PTL-30-499	250	0.750 (19.05)	1.500 (38.10)		18	7	5	16	8	5	
▶	PTL-31-427**	250	1.000 (25.40)	1.500 (38.10)	0.500 (12.70)	24	10	7	5	2	1	
▶	BPTL-31-427	2500	1.000 (25.40)	1.500 (38.10)	0.500 (12.70)	24	10	7	5	2	1	
▶	PTL-31-498	250	1.000 (25.40)	1.500 (38.10)		24	10	7	16	8	5	
▶	PTL-31-499	250	1.000 (25.40)	1.500 (38.10)		24	10	7	16	8	5	
▶	PTL-31-642	250	1.000 (25.40)	1.500 (38.10)	0.500 (12.70)	24	10	7	5	2	1	
▶	PTL-32-427**	250	1.500 (38.10)	1.500 (38.10)	0.500 (12.70)	37	15	10	5	2	1	
▶	BPTL-32-427	1000	1.500 (38.10)	1.500 (38.10)	0.500 (12.70)	37	15	10	5	2	1	
▶	BPTL-32-498	1000	1.500 (38.10)	1.500 (38.10)		37	15	10	5	2	1	
▶	PTL-88-427	250	1.750 (44.45)	1.500 (38.10)	0.500 (12.70)	40	16	11	5	2	1	
▶	PTL-102-427	250	0.500 (12.70)	1.250 (31.75)	0.375 (9.53)	11	5	3	3	1	1	
▶	PTL-103-427	250	1.000 (25.40)	1.250 (31.75)	0.500 (12.70)	24	10	7	5	2	1	
▶	PTL-106-427	1	continuous	1.500 (114.30)	0.500 (12.70)		N/A		5	2	1	
▶	PTL-107-427	100	2.000 (50.80)	1.500 (38.10)	0.500 (12.70)	46	19	13	5	2	1	
▶	BPTL-107-427	1000	2.000 (50.80)	1.500 (38.10)	0.500 (12.70)	46	19	13	5	2	1	
10 to 12 GAUGE WIRE (AWG) Based on THHN Wire - Maximum Wire Diameter - 0.210 in (5.30 mm)												
▶	PTL-16-498	500	0.375 (9.52)	1.000 (25.40)		8	3	2	10	5	3	
▶	PTL-16-499	500	0.375 (9.52)	1.000 (25.40)		8	3	2	10	5	3	
▶	PTL-17-427*	500	0.500 (12.70)	1.000 (25.40)	0.375 (9.53)	11	5	3	3	1	1	
▶	BPTL-17-427	5000	0.500 (12.70)	1.000 (25.40)	0.375 (9.53)	11	5	3	3	1	1	
▶	PTL-17-498	500	0.500 (12.70)	1.000 (25.40)		11	5	3	3	1	1	
▶	PTL-18-427*	250	0.750 (19.05)	1.000 (25.40)	0.375 (9.53)	18	7	5	3	1	1	
▶	BPTL-18-427	2500	0.750 (19.05)	1.000 (25.40)	0.375 (9.53)	18	7	5	3	1	1	
▶	PTL-18-498	250	0.750 (19.05)	1.000 (25.40)		18	7	5	10	5	3	
▶	BPTL-18-498	2500	0.750 (19.05)	1.000 (25.40)		18	7	5	10	5	3	
▶	PTL-18-499	250	0.750 (19.05)	1.000 (25.40)		18	7	5	10	5	3	
▶	PTL-19-427**	250	1.000 (25.40)	1.000 (25.40)	0.375 (9.53)	24	10	7	3	1	1	
▶	BPTL-19-427	2500	1.000 (25.40)	1.000 (25.40)	0.375 (9.53)	24	10	7	3	1	1	
▶	PTL-19-498	250	1.000 (25.40)	1.000 (25.40)		24	10	7	10	5	3	
▶	BPTL-19-498	2500	1.000 (25.40)	1.000 (25.40)		24	10	7	10	5	3	
▶	PTL-19-499	250	1.000 (25.40)	1.000 (25.40)		24	10	7	10	5	3	
▶	PTL-19-642	250	1.000 (25.40)	1.000 (25.40)	0.375 (9.53)	24	10	7	3	1	1	
▶	PTL-87-427	250	1.750 (44.45)	1.000 (25.40)	0.375 (9.53)	40	16	11	3	1	1	
▶	PTL-104-427	250	1.500 (38.10)	1.000 (25.40)	0.375 (9.53)	37	15	10	3	1	1	
10 to 16 GAUGE WIRE (AWG) Based on THHN Wire - Maximum Wire Diameter - 0.160 in (4.10 mm)												
▶	PTL-10-427*	750	0.250 (6.35)	0.750 (19.05)	0.375 (9.53)	5	2	1	3	1	1	
▶	PTL-10-498	750	0.250 (6.35)	0.750 (19.05)		5	2	1	3	1	1	
▶	PTL-11-427*	500	0.500 (12.70)	0.750 (19.05)	0.375 (9.53)	11	5	3	3	1	1	
▶	BPTL-11-427	5000	0.500 (12.70)	0.750 (19.05)	0.375 (9.53)	11	5	3	3	1	1	
▶	PTL-11-498	500	0.500 (12.70)	0.750 (19.05)		11	5	3	8	4	2	
▶	BPTL-11-498	5000	0.500 (12.70)	0.750 (19.05)		11	5	3	8	4	2	
▶	PTL-11-499	500	0.500 (12.70)	0.750 (19.05)		11	5	3	8	4	2	
▶	BPTL-11-499	5000	0.500 (12.70)	0.750 (19.05)		11	5	3	8	4	2	
▶	PTL-96-427	250	1.000 (25.40)	0.750 (19.05)	0.375 (9.53)	24	10	7	3	1	1	
16 to 22 GAUGE WIRE (AWG) Based on THHN Wire - Maximum Wire Diameter - 0.110 (2.80 mm)												
▶	PTL-7-498	500	0.500 (12.70)	0.500 (12.70)		11	5	3	5	2	1	
▶	PTL-7-499	500	0.500 (12.70)	0.500 (12.70)		11	5	3	5	2	1	

Tedlar® is a registered trademark of DuPont.

* Also available in: YL=Yellow

** Also available in: BL=blue, BR=brown, GR=green, GY=grey, OR=orange, PL=purple, RD=red, YL=yellow.
To order a color, add a dash "-" after the material number, then add the color suffix.

Standard product: Contact your Brady Identification Solutions distributor or Customer Service representative for ordering information.

PORTABLE PRINTERS AND LABELS

WIRE & CABLE MARKING

TLS2200 / TLS PC LINK LABELS