

HVAC Disconnects

Fused and Non-Fused

Series B22__



Metallic
Fused Disconnect



Metallic
Non-Fused Disconnect



Non-Metallic Disconnect

RAINPROOF AIR CONDITIONER PULLOUT UNITS

Fused and Non-Fused Features:

- NEMA 3R Rainproof.
- Compact design but offers ample working space.
- Internal shield can be removed without tools.
- Specifications are embossed on internal shield.
- Knockouts on back, bottom, and both sides.
- Touchproof construction.
- Padlockable
- Agency Approvals:
UL Listed to UL 1429
CUL Certified

METALLIC

Single Phase 2W, 240 Volts AC

UL Guide WGEW

Wire Range: #14 - #2 awg, Al-Cu wire

Main Rating	Catalog Number		Maximum HP ¹		Apprx. Dimensions H x W x D(in.)
			120V	240V	
30A**	B221-30F*	(Fused)	2	3	7-5/8 x 6-1/4 x 3-5/8
60A**	B222-60F*	(Fused)	3	10	7-5/8 x 6-1/4 x 3-5/8
60A***	B222-60NF	(Non-fused)	3	10	8-5/8 x 4-7/8 x 3-5/8
-	96-3258-4	Replacement Pullout Head			

*Suitable for use as service equipment with optional field installed lug kit Number DPF6

Shipping Weight - 2.7 lbs. per unit.

Case pack quantity 10, Case pack weight 30 lbs.

Carton Dimensions:

14-1/2" L x 11-1/2" W x 9-1/2" H; *14-3/4" L x 11-1/2" W x 9-1/2" H

NON-METALLIC

Single Phase 2W, 240 Volts AC

UL Guide WGEW

Material: Norell

Flammability Rating: 94 V-O

Wire Range: #14 - #2 awg, Al-Cu wire

Main Rating	Catalog Number		Maximum HP ¹		Apprx. Dimensions H x W x D (in.)
			120V	240V	
30A	B221-30FNM	(Fused)	2	3	8-5/8 x 5 x 3-1/2
60A	B222-60FNM	(Fused)	3	10	8-5/8 x 5 x 3-1/2
60A	B222-60NFNM	(Non-Fused)	3	10	8-5/8 x 5 x 3-1/2

Shipping Weight - 1.5 lbs. per unit.

Case pack quantity 10, Case pack weight 16 lbs.

Carton Dimensions: 21-3/8" L x 12-1/2" W x 10-1/2" H

¹Rated with Bussmann LPN-RK, FRN-R, DLN-R and HAC-R Dual Element Time Delay Fuses.

The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.