


LIMITRON® Fast-Acting Fuses 600 Volt, 1/10 - 30 Amps



Dimensional Data



- LIMITRON® fast-acting fuse.
- Melamine tube.
- Nickel-plated bronze endcaps.

CATALOG SYMBOL: KTK
FAST-ACTING
1/10 TO 30 AMPERES
600 VOLTS AC (OR LESS), 300 VOLTS DC (OR LESS)†
INTERRUPTING RATING—100,000A RMS SYM. (U.L.)
UL LISTED, STD. 248-14, (GUIDE #JDYX, FILE #E19180)
CSA CERTIFIED: C22.2 NO. 248.14
(FILE #53787—CLASS #1422-01)
HRC-MISC
†SELF-CERTIFIED RATING

Electrical Ratings (Catalog Symbol and Amperes)

600 Volts AC - U.L. Listed and C.S.A.

KTK-1/10	KTK-1	KTK-6	KTK-25
KTK-1/8	KTK-1-1/4	KTK-7	KTK-30
KTK-2/10	KTK-1-1/2	KTK-7-1/2	—
KTK-1/4	KTK-2	KTK-8	—
KTK-3/10	KTK-2-1/2	KTK-9	—
KTK-4/10	KTK-3	KTK-10	—
KTK-1/2	KTK-3-1/2	KTK-12	—
KTK-6/10	KTK-4	KTK-15	—
KTK-3/4	KTK-5	KTK-20	—

Carton Quantity and Weight


Ampere Ratings	Carton Qty.	Weight*	
		Lbs.	Kg.
1-30	10	.180	.082

*Weight per carton.

Fuseblock Catalog Numbers

Poles	Terminal Type		
	Screw With Quick Connect	Pressure Plate w/Quick Connect	Box Lug
1	BM6031SQ	BM6031PQ	BM6031B
2	BM6032SQ	BM6032PQ	BM6032B
3	BM6033SQ	BM6033PQ	BM6033B

Time-Current Characteristic Curves—Average Melt



CE logo denotes compliance with European Union Low Voltage Directive (50-1000 VAC, 75-1500 VDC). Refer to BIF document #8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.

The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.