
Restangular Connectors STA Series											
				S	TA 40 I	NSER	ΓS				
SCREW T	ERN	ΛINA	TION				;	SOLDER	TERMIN	IATION	
Communitie Communitie Communitie Communitie											
These inserts fit in the HA 32 Series Housings which are on the following pages.Screw Termination (2X) Solder Termination (2X)10.5031 									page 60.		
HA 32 HOODS WITH DOUBLE LEVER BOLTS											
Position of Cable Entry		e of E		PG	ard Grey C NPT	Metric	PG	oating (NE	Metric	Relief	
Top Entry	PG 21	3/4"	Metric 25	10.5820	Part # 10.5820NP	Part # 19.5820	Part # 70.5212	Part # 70.5212NP	Part # 79.5212	PG NPT M	
Side Entry	29 21 29	1" 3/4" 1"	32 25 32	10.5830 10.5760 10.5770	10.5830NP 10.5760NP 10.5770NP	19.5830 19.5760 19.5770	70.5214 70.5232 70.5234	70.5214NP 70.5232NP 70.5234NP	79.5214 79.5232 79.5234		
	2 S	URI	Stan	dard Grey 10.4720	UNT BA	ck Coating 70.50	(NEMA 4X 225 VITH C		E LEVI		
Number of Entries	Size of Entry		Size of Entry Standard Grey C PG NPT		oating Metric	Black C	oating (NE	NPT Metric			
1 Entry	PG 21 29	3/4" 1"	Metric 25 32	Part # 10.4740 10.4741	Part # 10.4740NP 10.4741NP	Part # 19.4740 19.4741	Part # 70.5072 70.5074	Part # 70.5072NP 70.5074NP	Part # 79.5072 79.5074	PG NPT M	
2 Entries	21 29	3/4" 1"	25 32	10.4820 10.4821	10.4820NP 10.4821NP	19.4820 19.4821	70.5082 70.5084	70.5082NP 70.5084NP	79.5082 79.5084		
HA 32	2 C	AB	LE C	OUPL	ER HO	ODS \	WITH	DOUBL	E LEV	ERS	
Profile	Siz	e of E	ntry	Standa	ard Grey C	oating	Black C	oating (NE	EMA 4X)	Strain Relief	

Destile	Siz	e of I	Entry	Standard Grey Coating			Black Coating (NEMA 4X)			Strain Relief
Profile	PG	NPT	Metric	PG Part #	NPT Part #	Metric Part #	PG Part #	NPT Part #	Metric Part #	PG NPT M
Standard	21 29	3/4" 1"	25 32	10.5880 10.5885	10.5880NP 10.5885NP	19.5880 19.5885	70.5110 70.5112	70.5110NP 70.5112NP	79.5110 79.5112	

www.contactelectronics.com 800-221-1451

		НА	32					onne ries			
HA 32 HOODS WITH DOUBLE LEVERS TOP ENTRY I I I I I I I I I I I I I I I I I I I											
	2	Ś	,	50 65 67.8		82 124.5			7		
Position of	Siz	e of E	Entry	Standa	ard Grey Co	82 124.5	Black C	coating (NE	EMA 4X)	Stra	
Position of Cable Entry		e of E		PG	NPT	oating Metric	Black C PG Part #	NPT	Metric	Stra Reli PG NP	
			Entry Metric 25	PG		ea taxis	PG	• •		Reli	
Cable Entry	PG	NPT	Metric	PG Part #	NPT Part #	oating Metric Part #	PG Part #	NPT Part #	Metric Part #	Reli	
Cable Entry	PG 21	NPT 3/4"	Metric 25	PG Part # 10.5840	NPT Part # 10.5840NP	exting Metric Part # 19.5840	PG Part # 70.5262	NPT Part # 70.5262NP	Metric Part # 79.5262	Reli	




Standard Grey CoatingWith CoverWithout Cover70.503010.4731

Black Coating (NEMA 4X) 70.5035

HA 32 SURFACE MOUNT BASES WITH DOUBLE LEVER BOLTS





Metric bases do not come with a neck.

Number of	Siz	e of l	Entry	Stand	ard Grey C	oating	Black Coating (NEMA 4X)			Strain Relief
Entries	PG	NPT	Metric	PG Part #	NPT Part #	Metric Part #	PG Part #	NPT Part #	Metric Part #	PG NPT M
1 Entry	21	3/4"	25	70.5152	70.5152NP	79.5152	70.5172	70.5172NP	79.5172	
	29	1"	32	70.5154	70.5154NP	79.5154	70.5174	70.5174NP	79.5174	
2 Entries	21	3/4"	25	70.5162	70.5162NP	79.5162	70.5182	70.5182NP	79.5182	
	29	1"	32	70.5164	70.5164NP	79.5164	70.5184	70.5184NP	79.5184	
				otor	etal	eet		loe	601	2

www.confactelectronics.com <u>800-221-1451</u>