

Features

Panel thermostat

- Small, compact size (17.5 mm wide)
- Snap action thermostatic Bimetal sensor
- Wide temperature setting range
- Long electrical life
- 35 mm rail (EN 60715) mount

NEW 7T.81.0.000.240x





• Heating control

NEW 7T.81.0.000.230x



• Ventilation control



Heating control - Should the panel temperature fall below the (minimum) set temperature the contact will close to call for heat. The contact will open when this set temperature is exceeded.

Ventilation control - Should the panel temperature exceed the (maximum) set temperature then the contact will close to call for cooling. The contact will open when the temperature falls below this set temperature.

For outline drawing see page 2

Contact specification				
Contact configuration	1 NC		1 NO	
Rated current/Maximum peak current A	10/10		10/10	
Rated voltage/Maximum switching voltage V AC	250/250		250/250	
Rated load AC1 VA	2,500		2,500	
Rated load AC15 (230 V AC) VA	250		250	
Single phase motor rating AC3 (230 V AC) kW	0.125		0.125	
Breaking capacity DC1: 30/110/220V A	1/0.3/0.15		1/0.3/0.15	
Minimum switching load mW (V/mA)	500 (12/10)		500 (12/10)	
Standard contact material	AgNi		AgNi	
Temperature setting range				
Setting range (ventilation) °C	-		-20...+40	+0...+60
Switch temperature differential K	-		7 ± 4	
Setting range (heating) °C	-20...+40	+0...+60	-	
Switch temperature differential K	7 ± 4		-	
Technical data				
Electrical life at rated load AC1 cycles	100·10 ³		100·10 ³	
Ambient temperature range °C	-45...+80		-45...+80	
Protection category	IP 20		IP 20	
Approvals (according to type)				

Ordering information

Example: 7T Series, thermostat for ventilation control, contact activates ventilation should the panel temperature exceed the set value (max+60°C), 35 mm rail (EN 60715) mount.

7 T . 8 1 . 0 . 0 0 0 . 2 3 0 3

Series ————
Type ————
 8 = 35 mm rail (EN 60715) mount
No. of contacts ————
 1 = 1 contact
Voltage type ————
 0 = No operating voltage required
Rated operating voltage ————
 000 = No operating voltage required

Control function
 (Temperature only)
 1 = (-20...+40)°C
 3 = (0...+60)°C
Contact configuration
 3 = 1 NO contact
 4 = 1 NC contact
Monitoring function
 2 = Temperature, adjustable

Technical data

Insulation			
Dielectric strength between open contacts	V AC	500	
Other data			
Screw torque	Nm	0.5	0.5
Max. wire size		solid cable	stranded cable
	mm ²	1x2.5	1x1.5
	AWG	1x12	1x16

Outline drawings

7T.81
Screw terminal

