

Double Row Terminal Blocks

200 Series Kulka® 671 GP Series

300 Volts



Specifications:

Base, General Purpose Phenolic, 150° C
 Closed Back Design
 Screws, #6-32 Binder Head, Phil-Slot
 Terminals, Plated Brass
 1-30 Poles
 7/16" Centers
 Wire Range with Wire Binding Screw #12 - #22 Awg - 20 Amps
 Wire Range with Sems Pressure Screw #12 - #22 Awg Stranded Copper Wire Only - 20 Amps
 Will Accommodate Lugs for Wire Sizes #10 - #16 Awg - 30 Amps
 The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.
 UL Recognized File No. E62806
 CSA Certified File No. LR19766
 CE

Catalog #	Catalog #	# of Poles	Dimensions		Catalog #	Catalog #	# of Poles	Dimensions	
			A	B				A	B
201	671 GP 01	1	1.19	.88	216	671 GP 16	16	7.75	7.44
202	671 GP 02	2	1.62	1.31	217	671 GP 17	17	8.19	7.88
203	671 GP 03	3	2.06	1.75	218	671 GP 18	18	8.62	8.31
204	671 GP 04	4	2.50	2.19	219	671 GP 19	19	9.06	8.75
205	671 GP 05	5	2.94	2.62	220	671 GP 20	20	9.50	9.19
206	671 GP 06	6	3.38	3.06	221	671 GP 21	21	9.94	9.62
207	671 GP 07	7	3.81	3.50	222	671 GP 22	22	10.38	10.06
208	671 GP 08	8	4.25	3.94	223	671 GP 23	23	10.81	10.50
209	671 GP 09	9	4.69	4.38	224	671 GP 24	24	11.25	10.94
210	671 GP 10	10	5.12	4.81	225	671 GP 25	25	11.69	11.38
211	671 GP 11	11	5.56	5.25	226	671 GP 26	26	12.12	11.81
212	671 GP 12	12	6.00	5.69	227	671 GP 27	27	12.56	12.25
213	671 GP 13	13	6.44	6.12	228	671 GP 28	28	13.00	12.69
214	671 GP 14	14	6.88	6.56	229	671 GP 29	29	13.44	13.12
215	671 GP 15	15	7.31	7.00	230	671 GP 30	30	13.88	13.56

