

Double Row Terminal Blocks

200 HB Series (High Barrier)

600 Volts

Specifications:

Base, General Purpose Phenolic, 150° C

Closed Back Design

Screws, #6-32 Binder Head, Phil-Slot

Terminals, Plated Brass

1-30 Poles

7/16" Centers

Wire Range with Wire Binding Screw #12-#22 Awg - 20 Amps

Wire Range with Sems Pressure Screw #12-#22 Awg Stranded Copper Wire Only - 20 Amps

Will Accommodate Lugs for Wire Sizes #10-#16 Awg - 30 Amps

The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.

UL Recognized File No. E62806

CSA Certified File No. LR19766

CE



Catalog #	# of Poles	Dimensions		Catalog #	# of Poles	Dimensions	
		A	B			A	B
201 HB	1	1.19	.88	216 HB	16	7.75	7.44
202 HB	2	1.62	1.31	217 HB	17	8.19	7.88
203 HB	3	2.06	1.75	218 HB	18	8.62	8.31
204 HB	4	2.50	2.19	219 HB	19	9.06	8.75
205 HB	5	2.94	2.62	220 HB	20	9.50	9.19
206 HB	6	3.38	3.06	221 HB	21	9.94	9.62
207 HB	7	3.81	3.50	222 HB	22	10.38	10.06
208 HB	8	4.25	3.94	223 HB	23	10.81	10.50
209 HB	9	4.69	4.38	224 HB	24	11.25	10.94
210 HB	10	5.12	4.81	225 HB	25	11.69	11.38
211 HB	11	5.56	5.25	226 HB	26	12.12	11.81
212 HB	12	6.00	5.69	227 HB	27	12.56	12.25
213 HB	13	6.44	6.12	228 HB	28	13.00	12.69
214 HB	14	6.88	6.56	229 HB	29	13.44	13.12
215 HB	15	7.31	7.00	230 HB	30	13.88	13.56

Top Mounted Hardware is .250" Wide

Hardware Options:

KT 37	=	Full Quick Connect (0° flat)
KT 38	=	Full Quick Connect (45° Bend)
KT 39	=	Full Quick Connect (90° Bend)
ST(S)	=	Full Solder
LL(J601)	=	Line to Line Jumper
3/4 ST(HS)	=	Half Solder
KT 43	=	Half Quick Connect (0° Flat)
KT 44	=	Half Quick Connect (45° Bend)
KT 45	=	Half Quick Connect (90° Bend)
SP(3765)	=	Sems Pressure Saddle Screw
SPSE (3767)	=	Sems Pressure Saddle Screw with External Tooth Lock Washer
L	=	Feed Thru Solder (.437)
LWW	=	Feed Thru Wire Wrap (.640)
Y	=	Feed Thru Solder (.625)
YSY	=	Feed Thru Solder (.437)

