

Double Row Terminal Blocks

300 Series Kulka® 672 GP Series

600 Volts



Specifications:

Base, General Purpose Phenolic, 150° C
 Closed Back Design
 Screws, #8-32 Binder Head, Phil-Slot
 Terminals, Plated Brass
 1-24 Poles
 9/16" Centers
 Wire Range with Wire Binding Screw #10 - #14 Awg - 30 Amps
 Wire Range with Sems Pressure Screw #10 - #22 Awg Stranded Copper Wire Only - 30 Amps
 Will Accommodate Lugs for Wire Sizes #10 - #16 Awg - 30 Amps
 The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.
 UL Recognized File No. E62806
 CSA Certified File No. LR19766
 CE

Catalog#	Catalog #	# of Poles	Dimensions		Catalog #	Catalog #	# of Poles	Dimensions	
			A	B				A	B
301	672 GP 01	1	1.53	1.12	313	672 GP 13	13	8.28	7.88
302	672 GP 02	2	2.09	1.69	314	672 GP 14	14	8.84	8.44
303	672 GP 03	3	2.66	2.25	315	672 GP 15	15	9.41	9.00
304	672 GP 04	4	3.22	2.81	316	672 GP 16	16	9.97	9.56
305	672 GP 05	5	3.78	3.38	317	672 GP 17	17	10.53	10.12
306	672 GP 06	6	4.34	3.94	318	672 GP 18	18	11.09	10.69
307	672 GP 07	7	4.91	4.50	319	672 GP 19	19	11.66	11.25
308	672 GP 08	8	5.47	5.06	320	672 GP 20	20	12.22	11.81
309	672 GP 09	9	6.03	5.62	321	672 GP 21	21	12.78	12.38
310	672 GP 10	10	6.59	6.19	322	672 GP 22	22	13.34	12.94
311	672 GP 11	11	7.16	6.75	323	672 GP 23	23	13.91	13.50
312	672 GP 12	12	7.72	7.31	324	672 GP 24	24	14.47	14.06

Top Mounted Hardware is .250" Wide

Hardware Options:

KT 55	=	Full Quick Connect (0° flat)
KT 56	=	Full Quick Connect (45° Bend)
KT 57	=	Full Quick Connect (90° Bend)
ST	=	Full Solder
LL	=	Line to Line Jumper
3/4 ST	=	Half Solder
KT 61	=	Half Quick Connect (0° Flat)
KT 62	=	Half Quick Connect (45° Bend)
KT 63	=	Half Quick Connect (90° Bend)
SP	=	Sems Pressure Saddle Screw
SPSE	=	Sems Pressure Saddle Screw with External Tooth Lock Washer
L	=	Feed Thru Solder (.468)
LWW	=	Feed Thru Wire Wrap (1.00)
Y	=	Feed Thru Solder (.437)
YSY	=	Feed Thru Solder (.625)

