

Class H Fuse Holder - 250 Volt

Specifications:

Patented Cool Clip® Design
UL Listed File No. E35113
CSA Cert. File No. LR21455
CE

30 & 60 Amp

Clip, Copper Alloy, Tin Plated

100 & 200 Amp

Clip, One Piece Aluminum, Tin Plated

400 & 600 Amp

Clip, Copper Alloy, Tin Plated



Catalog #:

Std.	Reinforced	Poles	Amps	Base Materials	Wire Range	Fuse Size
F30A1S	RF30A1S	1	30	Thermo-plastic	#10-#22 AWG CU	9/16" DIA BY 2 "
F30A2S	RF30A2S	2				
F30A3S	RF30A3S	3				
F30A1SP	RF30A1SP	1	30	Thermo-plastic	#10-#14 AWG CU	9/16" DIA BY 2 "
F30A2SP	RF30A2SP	2				
F30A3SP	RF30A3SP	3				
F30A1B	RF30A1B	1	30	Thermo-plastic	#6-#14 AWG CU	13/16" DIA BY 3"
F30A2B	RF30A2B	2				
F30A3B	RF30A3B	3				
F60A1SQ*	RF60A1SQ*	1	60	Thermo-plastic	#10-#22 AWG CU	13/16" DIA BY 3"
F60A2SQ*	RF60A2SQ*	2				
F60A3SQ*	RF60A3SQ*	3				
F60A1B	RF60A1B	1	60	Thermo-plastic	#2-#14 AWG CU #2-#14 AWG AL	1" DIA BY 5 7/8"
F60A2B	RF60A2B	2				
F60A3B	RF60A3B	3				
RF100A1B	SAME	1	100	Phenolic	#2/0-#14 AWG CU #2/0-#12 AWG AL	1" DIA BY 5 7/8"
RF100A2B	SAME	2				
RF100A3B	SAME	3				
F200A1BE	SAME	1	200	Polyester	250 MCM- #6 AWG CU AL	1 1/2" DIA BY 7 1/8"
F200A3BE	SAME	3				
RF400A1B	SAME	1	400	Phenolic	(2) 350 MCM- #10 AWG CU AL	2 13/32" DIA BY 8 5/8"
RF400A3B	SAME	3				
F600A1B	N/A	1	600	Phenolic	(2) 500 MCM- #1/0 AWG CU AL	2 29/32" DIA BY 10 3/8"
F600A3B	N/A	3				

*UL Recognized File No. E35113