

Double Row Terminal Blocks

400 Series

600 Volts

Specifications:

Base, General Purpose Phenolic, 150° C

Closed Back Design

Screws, #10-32 Binder Head, Phil-Slot

Terminals, Plated Brass

1-12 Poles

11/16" Centers

Wire Range with Wire Binding Screw #10 - #22 Awg - 30 Amps

Wire Range with Sems Pressure Screw #10 - #22 Awg Stranded Copper Wire Only - 30 Amps

Will Accommodate Lugs for Wire Sizes #6 - #16 Awg - 65 Amps

The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.

UL Recognized File No. E62806

CSA Certified File No. LR19766

CE



Catalog #	# of Poles	Dimensions		Catalog #	# of Poles	Dimensions	
		A	B			A	B
401	1	1.81	1.38	407	7	5.94	5.50
402	2	2.50	2.06	408	8	6.62	6.19
403	3	3.19	2.75	409	9	7.31	6.88
404	4	3.88	3.44	410	10	8.00	7.56
405	5	4.56	4.12	411	11	8.69	8.25
406	6	5.25	4.81	412	12	9.38	8.94

Hardware Options:

SP = Sems Pressure Saddle Screw

LL = Line to Line Jumper

