

Double Row Terminal Blocks

Kulka® 600 GP Series 300 Volts



Specifications:

Base, Phenolic, 150° C

JJ (GDI-30F) Material is Available

Open Back Design

Screws, #5-40 Binder Head, Phil-Slot

Terminals, Plated Brass

1-22 Poles

The Suitability of These Devices for Greater Currents or Voltage Requirements Shall be Determined in the End-Use Application

3/8" Centers

Wire Range with Wire Binding

Screw #12-#22 Awg - 15 Amps

UL Recognized File No. E47811

CSA Certified File No. LR19766

CE

Catalog #	# of Poles	Dimensions		Catalog#	# of Poles	Dimensions	
		A	B			A	B
600 GP 01	1	0.75	1.03	600 GP 12	12	4.88	5.16
600 GP 02	2	1.13	1.41	600 GP 13	13	5.25	5.53
600 GP 03	3	1.50	1.78	600 GP 14	14	5.63	5.91
600 GP 04	4	1.88	2.16	600 GP 15	15	6.00	6.28
600 GP 05	5	2.25	2.53	600 GP 16	16	6.38	6.66
600 GP 06	6	2.63	2.91	600 GP 17	17	6.75	7.03
600 GP 07	7	3.00	3.28	600 GP 18	18	7.13	7.41
600 GP 08	8	3.38	3.66	600 GP 19	19	7.50	7.78
600 GP 09	9	3.75	4.03	600 GP 20	20	7.88	8.16
600 GP 10	10	4.13	4.41	600 GP 21	21	8.25	8.53
600 GP 11	11	4.50	4.78	600 GP 22	22	8.63	8.91

Top Mounted Hardware is .187" Wide

Hardware Options:

- KT 19 = Full Quick Connect (0° flat)
- KT 20 = Full Quick Connect (45° Bend)
- KT 21 = Full Quick Connect (90° Bend)
- ST = Full Solder
- LL(J600) = Line to Line Jumper
- 3/4 ST = Half Solder
- KT 25 = Half Quick Connect (0° Flat)
- KT 26 = Half Quick Connect (45° Bend)
- KT 27 = Half Quick Connect (90° Bend)
- 3865 = Wire Clamp Screw
- Y = Feed Thru Solder (.312)
- YSY = Feed Thru Solder (.500)
- Z = Lug Over the Side (.625)

