

Double Row Terminal Blocks

Kulka® 600A GP Series 300 Volts



Specifications:

Base, Phenolic, 150° C
JJ (GDI-30F) Material is Available
Open Back Design
Screws, #6-32 Binder Head, Phil-Slot
Terminals, Plated Brass
1-22 Poles

3/8" Centers
Wire Range with Wire Binding
Screw #12-#22 Awg - 15 Amps
UL Recognized File No. E47811
CSA Certified File No. LR19766

CE

The Suitability of These Devices for Greater Currents or Voltage Requirements Shall be Determined in the End-Use Application

Catalog #	# of Poles	Dimensions		Catalog#	# of Poles	Dimensions	
		A	B			A	B
600A GP 01	1	0.75	1.03	600A GP 12	12	4.88	5.16
600A GP 02	2	1.13	1.41	600A GP 13	13	5.25	5.53
600A GP 03	3	1.50	1.78	600A GP 14	14	5.63	5.91
600A GP 04	4	1.88	2.16	600A GP 15	15	6.00	6.28
600A GP 05	5	2.25	2.53	600A GP 16	16	6.38	6.66
600A GP 06	6	2.63	2.91	600A GP 17	17	6.75	7.03
600A GP 07	7	3.00	3.28	600A GP 18	18	7.13	7.41
600A GP 08	8	3.38	3.66	600A GP 19	19	7.50	7.78
600A GP 09	9	3.75	4.03	600A GP 20	20	7.88	8.16
600A GP 10	10	4.13	4.41	600A GP 21	21	8.25	8.53
600A GP 11	11	4.50	4.78	600A GP 22	22	8.63	8.91

Top Mounted Hardware is .187" Wide

Hardware Options:

KT 19 = Full Quick Connect (0° flat)
KT 20 = Full Quick Connect (45° Bend)
KT 21 = Full Quick Connect (90° Bend)
ST = Full Solder
LL(J600) = Line to Line Jumper
3/4 ST = Half Solder
KT 25 = Half Quick Connect (0° Flat)
KT 26 = Half Quick Connect (45° Bend)
KT 27 = Half Quick Connect (90° Bend)
3865 = Wire Clamp Screw
Y = Feed Thru Solder (.312)
YSY = Feed Thru Solder (.500)
Z = Lug Over the Side (.625)

