

Double Row Terminal Blocks

Kulka® 602 GP Series

300 Volts

Specifications:

Base, General Purpose Phenolic, 150° C

JJ (GDI-30F) Material is Available

Open Back Design

Screws, #8-32 Binder Head, Phil-Slot

Terminals, Plated Brass

1-26 Poles

9/16" Centers

Wire Range with Wire Binding Screw #12 - #14 Awg - 30 Amps

The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.

UL Recognized File No. E47811

CSA Certified File No. LR19766

CE



Catalog #	# of Poles	Dimensions		Catalog #	# of Poles	Dimensions	
		A	B			A	B
602 GP 01	1	1.13	1.53	602 GP 14	14	8.44	8.84
602 GP 02	2	1.69	2.09	602 GP 15	15	9.00	9.41
602 GP 03	3	2.25	2.66	602 GP 16	16	9.56	9.97
602 GP 04	4	2.81	3.22	602 GP 17	17	10.13	10.53
602 GP 05	5	3.38	3.78	602 GP 18	18	10.69	11.09
602 GP 06	6	3.94	4.34	602 GP 19	19	11.25	11.66
602 GP 07	7	4.50	4.91	602 GP 20	20	11.81	12.22
602 GP 08	8	5.06	5.47	602 GP 21	21	12.38	12.78
602 GP 09	9	5.63	6.03	602 GP 22	22	12.94	13.34
602 GP 10	10	6.19	6.59	602 GP 23	23	13.50	13.91
602 GP 11	11	6.75	7.16	602 GP 24	24	14.06	14.47
602 GP 12	12	7.31	7.72	602 GP 25	25	14.63	15.03
602 GP 13	13	7.88	8.28	602 GP 26	26	15.19	15.59

Top Mounted Hardware is .250" Wide

Hardware Options:

KT 55	=	Full Quick Connect (0° flat)
KT 56	=	Full Quick Connect (45° Bend)
KT 57	=	Full Quick Connect (90° Bend)
ST	=	Full Solder
LL	=	Line to Line Jumper
3/4 ST	=	Half Solder
KT 61	=	Half Quick Connect (0° Flat)
KT 62	=	Half Quick Connect (45° Bend)
KT 63	=	Half Quick Connect (90° Bend)
3786	=	Wire Clamp Screw
Y	=	Feed Thru Solder (.500)
YSY	=	Feed Thru Solder (.672)
Z	=	Lug Over the Side (.609)

