

Double Row Terminal Blocks

Kulka® 603 GP Series

600 Volts

Specifications:

Base, General Purpose Phenolic, 150° C

JJ (GDI-30F) Material is Available

Open Back Design

Screws, #10-32 Binder Head, Phil-Slot

Terminals, Plated Brass

1-12 Poles

11/16" Centers

Wire Range with Wire Binding Screw #10 - #12 Awg - 50 Amps

Will Accommodate Lugs for Wire Sizes #6 - #16 Awg - 65 Amps

The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.

UL Recognized File No. E47811

CSA Certified File No. LR19766

CE



Catalog #	# of Poles	Dimensions		Catalog #	# of Poles	Dimensions	
		A	B			A	B
603 GP01	1	1.38	1.81	603 GP07	7	5.50	5.94
603 GP02	2	2.06	2.50	603 GP08	8	6.19	6.63
603 GP03	3	2.75	3.19	603 GP09	9	6.88	7.31
603 GP04	4	3.44	3.88	603 GP10	10	7.56	8.00
603 GP05	5	4.13	4.56	603 GP11	11	8.25	8.81
603 GP06	6	4.81	5.25	603 GP12	12	8.94	9.38

Hardware Options:

LL = Line to Line Jumper
Y = Feed Thru Solder (.60)

