

# Double Row Terminal Blocks

## 621 RZ Series 600 Volts



### Specifications:

Base, Thermoplastic, 110° C  
(U.L. RTI w/o IMPACT)  
Closed Back Design  
Screws, #6-32 Binder Head, Phil-Slot  
Terminals, Plated Brass  
1-30 Poles  
The Suitability of These Devices  
for Greater Currents or Voltage  
Requirements Shall be  
Determined in the End-Use Application

Flammability Rating 94 V-O  
7/16" Centers  
Wire Range with Wire Binding  
Screw #12 - #22 Awg - 20 Amps  
Wire Range with Sems Pressure  
Screw #12 - #22 Awg Stranded Copper Wire Only - 20 Amps  
Will Accommodate Lugs for Wire Sizes #10-#16 Awg - 30 Amps  
UL Recognized File No. E62806  
CSA Certified File No. LR19766  
C E

| Catalog # | # of Poles | Dimensions |      | Catalog#  | # of Poles | Dimensions |       |
|-----------|------------|------------|------|-----------|------------|------------|-------|
|           |            | A          | B    |           |            | A          | B     |
| 621 RZ 01 | 1          | 1.19       | .88  | 621 RZ 16 | 16         | 7.75       | 7.44  |
| 621 RZ 02 | 2          | 1.62       | 1.31 | 621 RZ 17 | 17         | 8.19       | 7.88  |
| 621 RZ 03 | 3          | 2.06       | 1.75 | 621 RZ 18 | 18         | 8.62       | 8.31  |
| 621 RZ 04 | 4          | 2.50       | 2.19 | 621 RZ 19 | 19         | 9.06       | 8.75  |
| 621 RZ 05 | 5          | 2.94       | 2.62 | 621 RZ 20 | 20         | 9.50       | 9.19  |
| 621 RZ 06 | 6          | 3.38       | 3.06 | 621 RZ 21 | 21         | 9.94       | 9.62  |
| 621 RZ 07 | 7          | 3.81       | 3.50 | 621 RZ 22 | 22         | 10.38      | 10.06 |
| 621 RZ 08 | 8          | 4.25       | 3.94 | 621 RZ 23 | 23         | 10.81      | 10.50 |
| 621 RZ 09 | 9          | 4.69       | 4.38 | 621 RZ 24 | 24         | 11.25      | 10.94 |
| 621 RZ 10 | 10         | 5.12       | 4.81 | 621 RZ 25 | 25         | 11.69      | 11.38 |
| 621 RZ 11 | 11         | 5.56       | 5.25 | 621 RZ 26 | 26         | 12.12      | 11.81 |
| 621 RZ 12 | 12         | 6.00       | 5.69 | 621 RZ 27 | 27         | 12.56      | 12.25 |
| 621 RZ 13 | 13         | 6.44       | 6.12 | 621 RZ 28 | 28         | 13.00      | 12.69 |
| 621 RZ 14 | 14         | 6.88       | 6.56 | 621 RZ 29 | 29         | 13.44      | 13.12 |
| 621 RZ 15 | 15         | 7.31       | 7.00 | 621 RZ 30 | 30         | 13.88      | 13.56 |

Top Mounted Hardware is .250" Wide

### Hardware Options:

KT 37 = Full Quick Connect (0° flat)  
KT 38 = Full Quick Connect (45° Bend)  
KT 39 = Full Quick Connect (90° Bend)  
ST = Full Solder  
LL = Line to Line Jumper  
3/4 ST = Half Solder  
KT 43 = Half Quick Connect (0° Flat)  
KT 44 = Half Quick Connect (45° Bend)  
KT 45 = Half Quick Connect (90° Bend)  
SP(3765) = Sems Pressure Saddle Screw  
SPSE(3767) = Sems Pressure Saddle Screw  
with External Tooth Lock Washer

