

Double Row Terminal Blocks

672 RZ Series

600 Volts



Specifications:

Base, Thermoplastic, 110° C (U.L. RTI w/o Impact)
 Flammability Rating: 94V-O
 Closed Back Design
 Screws, #8-32 Binder Head, Phil-Slot
 Terminals, Plated Brass
 1-24 Poles
 9/16" Centers
 Wire Range with Wire Binding Screw #10 - #14 Awg - 30 Amps
 Wire Range with Sems Pressure Screw #10 - 22 Awg Stranded Copper Wire Only - 30 Amps
 The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.
 UL Recognized File No. E47811
 CSA Certified File No. LR19766
 C€

Catalog #	# of Poles	Dimensions		Catalog #	# of Poles	Dimensions	
		A	B			A	B
672 RZ 01	1	1.54	1.13	672 RZ 13	13	8.29	7.88
672 RZ 02	2	2.10	1.69	672 RZ 14	14	8.85	8.44
672 RZ 03	3	2.66	2.25	672 RZ 15	15	9.41	9.00
672 RZ 04	4	3.22	2.81	672 RZ 16	16	9.97	9.56
672 RZ 05	5	3.79	3.38	672 RZ 17	17	10.54	10.13
672 RZ 06	6	4.35	3.94	672 RZ 18	18	11.09	10.68
672 RZ 07	7	4.91	4.50	672 RZ 19	19	11.66	11.25
672 RZ 08	8	5.47	5.06	672 RZ 20	20	12.22	11.81
672 RZ 09	9	6.04	5.63	672 RZ 21	21	12.79	12.38
672 RZ 10	10	6.60	6.19	672 RZ 22	22	13.35	12.94
672 RZ 11	11	7.16	6.75	672 RZ 23	23	13.91	13.50
672 RZ 12	12	7.73	7.32	672 RZ 24	24	14.47	14.06

Top Mounted Hardware is .250" Wide

Hardware Options:

KT 55	=	Full Quick Connect (0° flat)
KT 56	=	Full Quick Connect (45° Bend)
KT 57	=	Full Quick Connect (90° Bend)
ST (S)	=	Full Solder
LL(602J)	=	Line to Line Jumper
3/4 ST(HS)	=	Half Solder
KT 61	=	Half Quick Connect (0° Flat)
KT 62	=	Half Quick Connect (45° Bend)
KT 63	=	Half Quick Connect (90° Bend)
3786 (SP)	=	Sems Pressure Saddle Screw
3787 (SPSE)	=	Sems Pressure Saddle Screw with External Tooth Lock Washer

