

Double Row Terminal Blocks

Kulka® 600A/800A GP Series

300 Volts AC/DC (Class B)

600A Series only

150 Volts AC/DC (Class C)

600A and 800A Series



600A GP 06

Specifications:

- Base, Phenolic, 150°C (UL RTI)
- Open Back Design (Insulator Strip required for Voltage Rating - see page 112)
- JJ (GDI-30F) Material Available
- Screws, #6-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-22 Poles
- 3/8" Centers
- Wire Range With Wire Binding Screw
#12 - #22 AWG – 15 Amps
- 800A Series (Riveted KT's) - see page 105
- UL Recognized File No. XCFR2.E47811
- CSA Certified File No. LR19766
- **CE**
- RoHS Compliant

Double Row Terminal Blocks

| Kulka® Catalog # | # of poles | Dimensions | |
|---------------------|------------|------------|------|
| | | A | B |
| 600A GP 01 | 1 | 1.03 | 0.75 |
| 600A GP 02 | 2 | 1.41 | 1.13 |
| 600A GP 03 | 3 | 1.78 | 1.50 |
| 600A GP 04 | 4 | 2.16 | 1.88 |
| 600A GP 05 | 5 | 2.53 | 2.25 |
| 600A GP 06 | 6 | 2.91 | 2.63 |
| 600A GP 07 | 7 | 3.28 | 3.00 |
| 600A GP 08 | 8 | 3.66 | 3.38 |
| 600A GP 09 | 9 | 4.03 | 3.75 |
| 600A GP 10 | 10 | 4.41 | 4.13 |
| 600A GP 11 | 11 | 4.78 | 4.50 |
| 600A GP 12 | 12 | 5.16 | 4.88 |
| 600A GP 13 | 13 | 5.53 | 5.25 |
| 600A GP 14 | 14 | 5.91 | 5.63 |
| 600A GP 15 | 15 | 6.28 | 6.00 |
| 600A GP 16 | 16 | 6.66 | 6.38 |
| 600A GP 17 | 17 | 7.03 | 6.75 |
| 600A GP 18 | 18 | 7.41 | 7.13 |
| 600A GP 19 | 19 | 7.78 | 7.50 |
| 600A GP 20 | 20 | 8.16 | 7.88 |
| 600A GP 21 | 21 | 8.53 | 8.25 |
| 600A GP 22 | 22 | 8.91 | 8.63 |

mm=dim X 25.4

For electronic drawings or 2D/3D CAD data, submit request at www.marathonsp.com/drawings.html

Hardware Options:

(Hardware options may affect ratings - consult Customer Service)

| CATALOG # | PRODUCT DESCRIPTION | PAGE REFERENCE |
|------------|------------------------------------|----------------|
| MSP | KULKA | |
| | KT19 Full Quick Connect (0° Flat) | See Page 105 |
| | KT20 Full Quick Connect (45° Bend) | See Page 105 |
| | KT21 Full Quick Connect (90° Bend) | See Page 105 |
| | KT25 Half Quick Connect (0° Flat) | See Page 105 |
| | KT26 Half Quick Connect (45° Bend) | See Page 105 |
| | KT27 Half Quick Connect (90° Bend) | See Page 105 |
| | ST Full Solder | See Page 106 |
| | 3/4 ST Half Solder | See Page 106 |
| | Y Feed Thru Solder (.312) | See Page 106 |
| | YSY Feed Thru Solder (.500) | See Page 106 |
| | Z Lug Over the Side (.625) | See Page 106 |
| | J 600 Line to Line Jumper | See Page 107 |
| | 600 RJ(S) Multiple Position Jumper | See Page 107 |
| | 3860 Wire Clamp Screw, Brass | See Page 107 |
| | 3865 Wire Clamp Screw | See Page 107 |
| | 2002 Stud | See Page 109 |
| PSB | Phil-Slot Brass Screw | Consult C/S |

Quick Connects: .020" x .187"

See pages 104-115 for terminal block accessories

