

# Class T Fuse Holders - 300 Volt

## Specifications:

Have Been Tested and Approved for  
200,000 Amp Interrupting Capacity  
Patented Cool Clip® Design  
UL Listed File No. E35113  
CSA Certified File No. LR21455  
C €

### 30 & 60 Amp

Clip, Copper Alloy, Tin Plated, with  
Patented Reject Member

### 100 Amp

Connector, One Piece Aluminum with  
Integral Heat Sink, Tin Plated  
Bolt, 1/4"-20X1/2", 1/4" Belleville Washer

### 200 Amp

Connector, One Piece Aluminum with  
Integral Heat Sink, Tin Plated  
Bolt, 5/16"-18X 3/4" Hex Head,  
5/16" Belleville Washer

### 400 & 600 Amp

Connector, One Piece Aluminum with  
Integral Heat Sink, Tin Plated Bolt  
3/8"-16X3/4" Hex Head



## Catalog #:

<u>Std.</u>	<u>Reinforced</u>	<u>Poles</u>	<u>Amp</u>	<u>Base Material</u>	<u>Wire Range</u>	<u>Fuse Size</u>
T30A2B	RT30A2B	2	30	Phenolic	#2-#14 AWG CU	13/32" DIA
T30A3B	RT30A3B	3			#2-#12 AWG CU	BY 7/8"
T60A2B	RT60A2B	2	60	Phenolic	#2-#14 AWG CU	9/16" DIA
T60A3B	RT60A3B	3			#2-#12 AWG CU	BY 7/8"
T100A1B	N/A	1	100	Phenolic	#2/0-#14 AWG CU	13/16" DIA
T100A3B	N/A	3			#2/0-#12 AWG CU	BY 2 5/32"
T200A1B	N/A	1	200	Phenolic	250 MCM	1 1/16" DIA
T200A3B	N/A	3			#6 AWG CU AL	BY 2 7/16"
T400A1B	N/A	1	400	Phenolic	(2) 250 MCM- #6 AWG CU AL	1 11/32" DIA BY 2 3/4"
T600A1B	N/A	1	600	Phenolic	(2) 500 MCM- #6 AWG CU AL	1 39/64" DIA BY 3 1/16"