

Non-Reversing, Three Pole Contactors With AC Coil, Series CA4 (Open type only) ①

I_e [A]		Ratings for Switching AC Motors (AC2 / AC3 / AC4)										Auxiliary Contacts per Contactor		Open Type Catalog Number	Price
		kW (50 Hz)				UL/CSA HP (60 Hz)									
		230V	415V 400V	500V	690V	1 Ø		3 Ø							
115V	230V					200V	230V	460V	575V						
AC-3	AC-1	230V	400V	500V	690V	115V	230V	200V	230V	460V	575V	NO	NC		
9	20	12	9	7	~	.75	1.5	3	3	5	5	1	0	CA4-9-10-✱	52
												0	1	CA4-9-01-✱	52



CA4-9-01 contactor

Non-Reversing, Three Pole Contactors With DC Coil, Series CA4 (Open type only) ①②

I_e [A]		Ratings for Switching AC Motors (AC2 / AC3 / AC4)										Auxiliary Contacts per Contactor		Open Type Catalog Number	Price
		kW (50 Hz)				UL/CSA HP (60 Hz)									
			415V 400V	500V	690V	1 Ø		3 Ø							
AC-3	AC-1	230V	400V	500V	690V	115V	230V	200V	230V	460V	575V	NO	NC		
9	20	12	9	7	~	.75	1.5	3	3	5	5	1	0	CA4-9C-10-✱	72
												0	1	CA4-9C-01-✱	72



CA4-9C-10 contactor

Reversing, Three Pole Contactors With AC Coil, Series CAU4 (Open type only) ①

I_e [A]		Ratings for Switching AC Motors (AC2 / AC3 / AC4)										Auxiliary Contacts per Contactor		Open Type		Price
		kW (50 Hz)				UL/CSA HP (60 Hz)										
		230V	415V 400V	500V	690V	1 Ø		3 Ø						Catalog Number		
AC-3	AC-1	230V	400V	500V	690V	115V	230V	200V	230V	460V	575V	NO	NC ②	Number	Price	
9	20	12	9	7	~	.75	1.5	3	3	5	5	0	1	CAU4-9-02- $\times$ -LW	125	
												2	1	CAU4-9-42- $\times$ -PW	165	

Note: Reversing CA4 contactors with DC coils will not accept a mechanical interlock and are not available.

CAU4...LW Includes:

- Mechanical interlock

CAU4...PW Includes:

- Mechanical and electrical interlock ③
- Reversing power and control wiring (using Wiring Kit Cat.# KCR4)
- Top mount auxiliary contact block (Cat.# CS4-P20)



CAU4-9-42-*-PW reversing contactor

A.C. Coil Codes ①

A.C. Coil Code	Voltage Range	
	50 Hz	60 Hz
24	24V	24V
120	110V	110V-120V
240	220V-230V	230V-240V
277	240V	277V
380	400V-415V	380V-400V

D.C. Coil Codes ①

D.C. Coil Codes	Voltage
24D	24V
48D	48V
110D	110V
220D	220V

Ordering Instructions

- Specify Catalog Number
- Replace (*) With Coil Code

See Coil Code table
on this page for codes

- ① CA4 not available without coil. Coils and contacts not replaceable.
- ② Select Coil Code from D.C. Coil Code table only.
- ③ NC contacts on each contactor are used for electrical interlocking.