





Pin headers SL-SMT 5.08/90G

new



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	13	15	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 215

Solder pin length 1.5 mm
Tape-on-Reel
Color
Tape width 56 mm

Poles	Type	Part No.	Qty.
2	SL-SMT 5.08/2/90G	1775004001	250
3	SL-SMT 5.08/3/90G	1775014001	250
4	SL-SMT 5.08/4/90G	1775024001	250
5	SL-SMT 5.08/5/90G	1775034001	250
6	SL-SMT 5.08/6/90G	1775044001	250
7	SL-SMT 5.08/7/90G	1775054001	250

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Other pole numbers and tape widths on request. Minimum order quantities may apply.

Accessories	Page
Mounting	189
Marking	190
Coding	193
Miscellaneous	198

Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	13	15	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 215

Solder pin length 1.5 mm
Tray
Color

Poles	Type	Part No.	Qty.
2	SL-SMT 5.08/2/90G	1775023001	66
3	SL-SMT 5.08/3/90G	1775033001	54
4	SL-SMT 5.08/4/90G	1775043001	48
5	SL-SMT 5.08/5/90G	1775053001	42
6	SL-SMT 5.08/6/90G	1775063001	36
7	SL-SMT 5.08/7/90G	1775073001	30
8	SL-SMT 5.08/8/90G	1775083001	30
9	SL-SMT 5.08/9/90G	1775093001	24
10	SL-SMT 5.08/10/90G	1775103001	24

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Other pole numbers available on request. Minimum order quantities may apply.

Accessories	Page
Mounting	189
Marking	190
Coding	193
Miscellaneous	198

Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	13	15	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 215

Solder pin length 1.5 mm
Standard box
Color

Poles	Type	Part No.	Qty.
2	SL-SMT 5.08/2/90G	1775002001	100
3	SL-SMT 5.08/3/90G	1775012001	100
4	SL-SMT 5.08/4/90G	1775022001	100
5	SL-SMT 5.08/5/90G	1775032001	50
6	SL-SMT 5.08/6/90G	1775042001	50
7	SL-SMT 5.08/7/90G	1775052001	50
8	SL-SMT 5.08/8/90G	1775062001	36
9	SL-SMT 5.08/9/90G	1775072001	50
10	SL-SMT 5.08/10/90G	1775082001	50
11	SL-SMT 5.08/11/90G	1775092001	50
12	SL-SMT 5.08/12/90G	1775102001	50
13	SL-SMT 5.08/13/90G	1775112001	50
14	SL-SMT 5.08/14/90G	1775122001	50
15	SL-SMT 5.08/15/90G	1775132001	50
16	SL-SMT 5.08/16/90G	1775142001	50
17	SL-SMT 5.08/17/90G	1775152001	20
18	SL-SMT 5.08/18/90G	1775162001	20
19	SL-SMT 5.08/19/90G	1775172001	20
20	SL-SMT 5.08/20/90G	1775182001	20
21	SL-SMT 5.08/21/90G	1775192001	20
22	SL-SMT 5.08/22/90G	1775202001	20
23	SL-SMT 5.08/23/90G	1775212001	20
24	SL-SMT 5.08/24/90G	1775222001	20

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Accessories	Page
Mounting	189
Marking	190
Coding	193
Miscellaneous	198