




Pin headers SL 7.62/90



Technical data	VDE	UL	CSA
Rated voltage (V)	500*	300	300
Rated current (A)	15	15	15


*Pollution severity 3 / Overvoltage category III
Additional technical data see page 225

Solder pin length 3.2 mm 4.5 mm

Color				
Poles	Type	Part No.	Part No.	Qty.
2	SL 7.62/2/90	1624150000	1623820000	100
3	SL 7.62/3/90	1624160000	1623830000	100
4	SL 7.62/4/90	1624170000	1623840000	100
5	SL 7.62/5/90	1624180000	1623850000	50
6	SL 7.62/6/90	1624190000	1623860000	50
7	SL 7.62/7/90	1624200000	1623870000	50
8	SL 7.62/8/90	1624210000	1623880000	50
9	SL 7.62/9/90	1624220000	1623890000	50
10	SL 7.62/10/90	1624230000	1623900000	50
11	SL 7.62/11/90	1624240000	1623910000	50
12	SL 7.62/12/90	1624250000	1623920000	50

Accessories	Page
Mounting	–
Marking	190
Coding	193
Miscellaneous	–

Pin headers SL 7.62/90B



Technical data	VDE	UL	CSA
Rated voltage (V)	500*	300	300
Rated current (A)	15	15	15

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 225

Solder pin length 3.2 mm 4.5 mm

Color				
Poles	Type	Part No.	Part No.	Qty.
2	SL 7.62/2/90B	1624370000	1624040000	100
3	SL 7.62/3/90B	1624380000	1624050000	100
4	SL 7.62/4/90B	1624390000	1624060000	100
5	SL 7.62/5/90B	1624400000	1624070000	50
6	SL 7.62/6/90B	1624410000	1624080000	50
7	SL 7.62/7/90B	1624420000	1624090000	50
8	SL 7.62/8/90B	1624430000	1624100000	50
9	SL 7.62/9/90B	1624440000	1624110000	50
10	SL 7.62/10/90B	1624450000	1624120000	50
11	SL 7.62/11/90B	1624460000	1624130000	50
12	SL 7.62/12/90B	1624470000	1624140000	50

Accessories	Page
Mounting	187*
Marking	190
Coding	193
Miscellaneous	–

* See Note, page 187