



Omnimate Range - 3.50 mm Pitch



Pin headers SL-SMT 3.5/180G

new



Technical data	VDE	UL	CSA
Rated voltage (V)	125*	300	300
Rated current (A)	13	10	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 211

Solder pin length	1.5 mm
Tape-on-Reel	
Color	
Tape width	56 mm 32 mm

Poles	Type	Part No.	Part No.	Qty.
2	SL-SMT 3.5/2/180G	1752984001	1752984002	200
3	SL-SMT 3.5/3/180G	1752994001	1752994002	200
4	SL-SMT 3.5/4/180G	1753004001	1753004002	200
5	SL-SMT 3.5/5/180G	1753014001	1753014002	200
6	SL-SMT 3.5/6/180G	1753024001	–	200
7	SL-SMT 3.5/7/180G	1753034001	–	200
8	SL-SMT 3.5/8/180G	1753044001	–	200
9	SL-SMT 3.5/9/180G	1753054001	–	200
10	SL-SMT 3.5/10/180G	1753064001	–	200
11	SL-SMT 3.5/11/180G	1753074001	–	200

Open end versions are also available. Please consult factory.
For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Accessories	Page
Mounting	189
Marking	190
Coding	193
Miscellaneous	–

Technical data	VDE	UL	CSA
Rated voltage (V)	125*	300	300
Rated current (A)	13	10	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 211

Solder pin length	1.5 mm
Tray	
Color	

Poles	Type	Part No.	Qty.
2	SL-SMT 3.5/2/180G	1762983001	108
3	SL-SMT 3.5/3/180G	1762993001	108
4	SL-SMT 3.5/4/180G	1753003001	96
5	SL-SMT 3.5/5/180G	1753013001	84
6	SL-SMT 3.5/6/180G	1753023001	72
7	SL-SMT 3.5/7/180G	1753033001	60
8	SL-SMT 3.5/8/180G	1753043001	54
9	SL-SMT 3.5/9/180G	1753053001	48
10	SL-SMT 3.5/10/180G	1753063001	42
11	SL-SMT 3.5/11/180G	1753073001	42
12	SL-SMT 3.5/12/180G	1753083001	36
13	SL-SMT 3.5/13/180G	1753093001	36
14	SL-SMT 3.5/14/180G	1753103001	30
15	SL-SMT 3.5/15/180G	1753113001	30
16	SL-SMT 3.5/16/180G	1753123001	24
17	SL-SMT 3.5/17/180G	1753133001	24
18	SL-SMT 3.5/18/180G	1753143001	24
19	SL-SMT 3.5/19/180G	1753153001	24
20	SL-SMT 3.5/20/180G	1753163001	24
21	SL-SMT 3.5/21/180G	1753173001	18
22	SL-SMT 3.5/22/180G	1753183001	18
23	SL-SMT 3.5/23/180G	1753193001	18
24	SL-SMT 3.5/24/180G	1753203001	18

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Accessories	Page
Mounting	189
Marking	190
Coding	193
Miscellaneous	–

Technical data	VDE	UL	CSA
Rated voltage (V)	125*	300	300
Rated current (A)	13	10	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 211

Solder pin length	1.5 mm
Standard box	
Color	

Poles	Type	Part No.	Qty.
2	SL-SMT 3.5/2/180G	1752982001	100
3	SL-SMT 3.5/3/180G	1752992001	100
4	SL-SMT 3.5/4/180G	1753002001	100
5	SL-SMT 3.5/5/180G	1753012001	50
6	SL-SMT 3.5/6/180G	1753022001	50
7	SL-SMT 3.5/7/180G	1753032001	50
8	SL-SMT 3.5/8/180G	1753042001	50
9	SL-SMT 3.5/9/180G	1753052001	50
10	SL-SMT 3.5/10/180G	1753062001	50
11	SL-SMT 3.5/11/180G	1753072001	50
12	SL-SMT 3.5/12/180G	1753082001	50
13	SL-SMT 3.5/13/180G	1753092001	50
14	SL-SMT 3.5/14/180G	1753102001	50
15	SL-SMT 3.5/15/180G	1753112001	50
16	SL-SMT 3.5/16/180G	1753122001	50
17	SL-SMT 3.5/17/180G	1753132001	20
18	SL-SMT 3.5/18/180G	1753142001	20
19	SL-SMT 3.5/19/180G	1753152001	20
20	SL-SMT 3.5/20/180G	1753162001	20
21	SL-SMT 3.5/21/180G	1753172001	20
22	SL-SMT 3.5/22/180G	1753182001	20
23	SL-SMT 3.5/23/180G	1753192001	20
24	SL-SMT 3.5/24/180G	1753202001	20

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Accessories	Page
Mounting	189
Marking	190
Coding	193
Miscellaneous	–