





Pin headers SL-SMT 3.5/180LF

new



Technical data	VDE	UL	CSA
Rated voltage (V)	125*	300	300
Rated current (A)	13	10	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 211

Solder pin length 1.5 mm

Tape-on-Reel

Color

Tape width 56 mm 32 mm

Poles	Type	Part No.	Part No.	Qty.
2	SL-SMT 3.5/2/180LF	1760964001	1760964002	200
3	SL-SMT 3.5/3/180LF	1760974001	1760974002	200
4	SL-SMT 3.5/4/180LF	1760984001	-	200
5	SL-SMT 3.5/5/180LF	1760994001	-	200
6	SL-SMT 3.5/6/180LF	1761004001	-	200
7	SL-SMT 3.5/7/180LF	1761014001	-	200
8	SL-SMT 3.5/8/180LF	1761024001	-	200
9	SL-SMT 3.5/9/180LF	1761034001	-	200

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Accessories	Page
Mounting	188, 189
Marking	190
Coding	193
Miscellaneous	-

Technical data	VDE	UL	CSA
Rated voltage (V)	125*	300	300
Rated current (A)	13	10	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 211

Solder pin length 1.5 mm

Tray

Color

Poles	Type	Part No.	Qty.
2	SL-SMT 3.5/2/180LF	1760963001	96
3	SL-SMT 3.5/3/180LF	1760973001	84
4	SL-SMT 3.5/4/180LF	1760983001	72
5	SL-SMT 3.5/5/180LF	1760993001	60
6	SL-SMT 3.5/6/180LF	1761003001	54
7	SL-SMT 3.5/7/180LF	1761013001	48
8	SL-SMT 3.5/8/180LF	1761023001	42
9	SL-SMT 3.5/9/180LF	1761033001	42
10	SL-SMT 3.5/10/180LF	1761043001	36
11	SL-SMT 3.5/11/180LF	1761053001	36
12	SL-SMT 3.5/12/180LF	1761063001	30
13	SL-SMT 3.5/13/180LF	1761073001	30
14	SL-SMT 3.5/14/180LF	1761083001	24
15	SL-SMT 3.5/15/180LF	1761093001	24
16	SL-SMT 3.5/16/180LF	1761103001	24
17	SL-SMT 3.5/17/180LF	1761113001	24
18	SL-SMT 3.5/18/180LF	1761123001	24
19	SL-SMT 3.5/19/180LF	1761133001	18
20	SL-SMT 3.5/20/180LF	1761143001	18
21	SL-SMT 3.5/21/180LF	1761153001	18
22	SL-SMT 3.5/22/180LF	1761163001	18
23	SL-SMT 3.5/23/180LF	1761173001	18
24	SL-SMT 3.5/24/180LF	1761183001	18

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Accessories	Page
Mounting	188, 189
Marking	190
Coding	193
Miscellaneous	-

Technical data	VDE	UL	CSA
Rated voltage (V)	125*	300	300
Rated current (A)	13	10	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 211

Solder pin length 1.5 mm

Standard box

Color

Poles	Type	Part No.	Qty.
2	SL-SMT 3.5/2/180LF	1760962001	100
3	SL-SMT 3.5/3/180LF	1760972001	100
4	SL-SMT 3.5/4/180LF	1760982001	100
5	SL-SMT 3.5/5/180LF	1760992001	50
6	SL-SMT 3.5/6/180LF	1761002001	50
7	SL-SMT 3.5/7/180LF	1761012001	50
8	SL-SMT 3.5/8/180LF	1761022001	50
9	SL-SMT 3.5/9/180LF	1761032001	50
10	SL-SMT 3.5/10/180LF	1761042001	50
11	SL-SMT 3.5/11/180LF	1761052001	50
12	SL-SMT 3.5/12/180LF	1761062001	50
13	SL-SMT 3.5/13/180LF	1761072001	50
14	SL-SMT 3.5/14/180LF	1761082001	50
15	SL-SMT 3.5/15/180LF	1761092001	50
16	SL-SMT 3.5/16/180LF	1761102001	50
17	SL-SMT 3.5/17/180LF	1761112001	20
18	SL-SMT 3.5/18/180LF	1761122001	20
19	SL-SMT 3.5/19/180LF	1761132001	20
20	SL-SMT 3.5/20/180LF	1761142001	20
21	SL-SMT 3.5/21/180LF	1761152001	20
22	SL-SMT 3.5/22/180LF	1761162001	20
23	SL-SMT 3.5/23/180LF	1761172001	20
24	SL-SMT 3.5/24/180LF	1761182001	20

For detailed product and application information for SMT see chapter "Other Applications" page 176-183.

Accessories	Page
Mounting	188, 189
Marking	190
Coding	193
Miscellaneous	-