


Omnimate Range - 5.08 mm Pitch



Socket blocks BL 5.08/180



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	8	10	15
Wire size (mm ² /AWG)	1.5	22...12	26...14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 218

Color



Poles	Type	Part No.	Part No.	Qty.
2	BL 5.08/2/180	1716320000	1716470000	100
3	BL 5.08/3/180	1716330000	1716480000	100
4	BL 5.08/4/180	1716340000	1716490000	100
5	BL 5.08/5/180	1716350000	1716500000	50
6	BL 5.08/6/180	1716360000	1716510000	50
7	BL 5.08/7/180	1716370000	1716520000	50
8	BL 5.08/8/180	1716380000	1716530000	50
9	BL 5.08/9/180	1716390000	1716540000	50
10	BL 5.08/10/180	1716400000	1716550000	50
11	BL 5.08/11/180	1716410000	1716560000	50
12	BL 5.08/12/180	1716420000	1716570000	50
13	BL 5.08/13/180	1716430000	1716580000	50
14	BL 5.08/14/180	1716440000	1716590000	50
15	BL 5.08/15/180	1716450000	1716600000	50
16	BL 5.08/16/180	1716460000	1716610000	50

Due to torque requirements do not connect wires to socket when connectors are already mated!

Accessories	Page
Mounting	–
Marking	190
Coding	–
Miscellaneous	195-201