





LM 5.00/90



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	17.5	10	10
Wire size (mm ² /AWG)	1.5	24...12	14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 53



Solder pin length 3.5 mm 3.5 mm

Color

Poles	Type	Part No.	Part No.	Qty.
2	LM 5.00/2/90	1715310000	1715250000	500
3	LM 5.00/3/90	1715320000	1715260000	500
4	LM 5.00/4/90	-	999330	
5	LM 5.00/5/90	-	999331	
6	LM 5.00/6/90	-	999332	
7	LM 5.00/7/90	-	999333	
8	LM 5.00/8/90	-	999334	
9	LM 5.00/9/90	-	999335	
10	LM 5.00/10/90	-	999336	
11	LM 5.00/11/90	-	999337	
12	LM 5.00/12/90	-	999338	
13	LM 5.00/13/90	-	999339	
14	LM 5.00/14/90	-	999340	
15	LM 5.00/15/90	-	999341	
16	LM 5.00/16/90	-	999342	
17	LM 5.00/17/90	-	999343	
18	LM 5.00/18/90	-	999344	
19	LM 5.00/19/90	-	999345	
20	LM 5.00/20/90	-	999346	
21	LM 5.00/21/90	-	999347	
22	LM 5.00/22/90	-	999348	
23	LM 5.00/23/90	-	999349	
24	LM 5.00/24/90	-	999350	

Accessories	Page
Marking	42
Mounting	-
Miscellaneous	45

LM 5.00/135



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	17.5	10	10
Wire size (mm ² /AWG)	1.5	24...12	14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 53



Solder pin length 3.5 mm 3.5 mm

Color

Poles	Type	Part No.	Part No.	Qty.
2	LM 5.00/2/135	1715350000	1715290000	500
3	LM 5.00/3/135	1715360000	1715300000	500
4	LM 5.00/4/135	-	999351	
5	LM 5.00/5/135	-	999352	
6	LM 5.00/6/135	-	999353	
7	LM 5.00/7/135	-	999354	
8	LM 5.00/8/135	-	999355	
9	LM 5.00/9/135	-	999356	
10	LM 5.00/10/135	-	999357	
11	LM 5.00/11/135	-	999358	
12	LM 5.00/12/135	-	999359	
13	LM 5.00/13/135	-	999360	
14	LM 5.00/14/135	-	999361	
15	LM 5.00/15/135	-	999362	
16	LM 5.00/16/135	-	999363	
17	LM 5.00/17/135	-	999364	
18	LM 5.00/18/135	-	999365	
19	LM 5.00/19/135	-	999366	
20	LM 5.00/20/135	-	999367	
21	LM 5.00/21/135	-	999368	
22	LM 5.00/22/135	-	999369	
23	LM 5.00/23/135	-	999370	
24	LM 5.00/24/135	-	999371	

Accessories	Page
Marking	42
Mounting	-
Miscellaneous	45

LM 5.00/180



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	17.5	10	10
Wire size (mm ² /AWG)	1.5	24...12	14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 53

Solder pin length 3.5 mm 3.5 mm

Color

Poles	Type	Part No.	Part No.	Qty.
2	LM 5.00/2/180	1715330000	1715270000	500
3	LM 5.00/3/180	1715340000	1715280000	500
4	LM 5.00/4/180	-	999372	
5	LM 5.00/5/180	-	999373	
6	LM 5.00/6/180	-	999374	
7	LM 5.00/7/180	-	999375	
8	LM 5.00/8/180	-	999376	
9	LM 5.00/9/180	-	999377	
10	LM 5.00/10/180	-	999378	
11	LM 5.00/11/180	-	999379	
12	LM 5.00/12/180	-	999380	
13	LM 5.00/13/180	-	999381	
14	LM 5.00/14/180	-	999382	
15	LM 5.00/15/180	-	999383	
16	LM 5.00/16/180	-	999384	
17	LM 5.00/17/180	-	999385	
18	LM 5.00/18/180	-	999386	
19	LM 5.00/19/180	-	999387	
20	LM 5.00/20/180	-	999388	
21	LM 5.00/21/180	-	999389	
22	LM 5.00/22/180	-	999390	
23	LM 5.00/23/180	-	999391	
24	LM 5.00/24/180	-	999391	

Accessories	Page
Marking	42
Mounting	-
Miscellaneous	45