



modular
construction

TOP 4GS 6.35/90

new





Technical data	VDE	UL	CSA
Rated voltage (V)	320*	300	300
Rated current (A)	36	30	25
Wire size (mm ² /AWG)	6.0	22...10	10

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 63

TOP 4GS 6.35/180

new



Technical data	VDE	UL	CSA
Rated voltage (V)	320*	300	300
Rated current (A)	36	30	25
Wire size (mm ² /AWG)	6.0	22...10	10

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 63

Solder pin length 3.5 mm 3.5 mm

Color

Poles	Type	Part No.	Part No.	Qty.
2	TOP 4GS 6.35/2/90	1401760000	1786110000	100
3	TOP 4GS 6.35/3/90	1650300000	0265910000	100
4	TOP 4GS 6.35/4/90	1786030000	1536210000	50
5	TOP 4GS 6.35/5/90	1786040000	0308410000	50
6	TOP 4GS 6.35/6/90	1786050000	1786120000	50
7	TOP 4GS 6.35/7/90	1786060000	1786130000	50
8	TOP 4GS 6.35/8/90	1667910000	1786140000	50
9	TOP 4GS 6.35/9/90	1786070000	1786150000	50
10	TOP 4GS 6.35/10/90	1786080000	1786160000	50
11	TOP 4GS 6.35/11/90	1786090000	1786170000	50
12	TOP 4GS 6.35/12/90	1786100000	1786180000	50

Accessories	Page
Marking	41
Mounting	-
Miscellaneous	45

Solder pin length 3.5 mm 3.5 mm

Color

Poles	Type	Part No.	Part No.	Qty.
2	TOP 4GS 6.35/2/180	1786190000	1786300000	100
3	TOP 4GS 6.35/3/180	1786200000	1786310000	100
4	TOP 4GS 6.35/4/180	1786210000	1786320000	50
5	TOP 4GS 6.35/5/180	1786220000	1786330000	50
6	TOP 4GS 6.35/6/180	1786230000	1786340000	50
7	TOP 4GS 6.35/7/180	1786240000	1786350000	50
8	TOP 4GS 6.35/8/180	1786250000	1786360000	50
9	TOP 4GS 6.35/9/180	1786260000	1786370000	50
10	TOP 4GS 6.35/10/180	1786270000	1786380000	50
11	TOP 4GS 6.35/11/180	1786280000	1786390000	50
12	TOP 4GS 6.35/12/180	1786290000	1786400000	50

Accessories	Page
Marking	41
Mounting	-
Miscellaneous	45