



Screw Clamp 35 mm DIN-Rail Terminals

Neutral

WNT 16N

WNT 70N



Available Options	Version	WNT 16N	WNT 70N
For 10 x 3 busbars	Blue Wemid	1019000000	9512210000
For 6 x 6 busbars	Blue Wemid	on request	
Dimensions			
Width / Length / Height mm (in.)	with TS 35 x 7.5	12/60/47 (.47/2.36/1.85)	20.5/75/86 (.81/2.95/3.39)
	with TS 32	-	20.5/75/93.5 (.81/2.95/3.68)
Insulation stripping length	mm (in.)	12 (.47)	22 (.87)
Technical Data			
Rated voltage / rated current / wire size	UL		600 V / 175 A / #8...2/0 AWG [‡]
	CSA		600 V / 65 A / #8...2/0 AWG [‡]
	VDE	400 V / 76 A / 16 mm ²	400 V / 192 A / 70 mm ²
Torque	Nm (lb. in.)	2.3 (20.4)	9.9 (87.0)
Clamping screw	M	4	8
Support Bracket			
	WHP for 10 x 3 SSch	Type	Part No.
	Blue Wemid	WHP 2.5...10	1050280000
	Thickness 1.5 mm	WHP 2.5...10	1050280000
Busbar			
	10 x 3	SSch 10x3 Cu	0348900000
		SSch 10x3 Brass	0259800000
Clamping Yoke			
	For 10 x 3 SSch	ZB 4 K [*]	0475380000
		ZBE 6 K ^{**}	0525980000
		ZB 16 K [†]	0502880000
		ZB 35 K ^{††}	0502680000
Supply via clamping yoke, for example			
Test Plugs			
	For #18 AWG wire	PS 2.3	0180400000
	For #12 AWG wire		PS 4 0299600000 insertable in screwhead of clamp
Marking Tags			
Note: Part numbers shown are for a single card of pre-printed tags numbered 1-50. For additional information, see Accessories section.	Consecutive horizontal	DEK 5/5	0473460001
	Consecutive vertical	DEK 5/5	0473560001

* (0.5...4) mm²
 ** (1.5...10) mm²
 † (2.5...16) mm²
 †† (16...35) mm²
 ‡ Pending