


Circuit Protection Terminals

Warning:

- Install AP partition after last ASK 1 or KDKS 1.
- Disconnect power before replacing the fuse.



Fuse terminals are available with LED blown fuse indicators, which speed identification of fuse failures and reduces costly down time. The maximum operating voltage for the indicator fuse blocks is determined by the LED's rating.


A 2 mA residual current passes through the LED when the fuse is blown, unless otherwise indicated.

WTR 2.5/SI new
with fuse holder
for G fuse cartridges 5x20



Pluggable Fuse, Single Level
5 x 20 mm fuse

WTR 4 SI new
with fuse holder
for G fuse cartridges 5x20



Pluggable Fuse, Single Level
5 x 20 mm fuse

Terminal Block Selection Data			
Available Options		Version	Part No.
		Beige Wemid	1763940000
		10 VDC-36 VAC Beige Wemid/LED	1763950000
		35 VDC-70 VAC Beige Wemid/LED	1763960000
		60 VDC-150 VAC Beige Wemid/LED	1763970000
		140 VDC-250 VAC Beige Wemid/LED	1763980000
Dimensions			
Width / Length / Height mm (in.)	for TS 35	5/60/83 (.20/2.36/3.27)	6/60/82 (.24/2.36/3.23)
Insulation stripping length	mm (in.)	10 (.39)	13 (.51)
Technical Data			
Rated voltage / rated current / wire size	UL	300 V / 10 A / #22...12 AWG	300 V / 6.3 A / #22...10 AWG
	CSA	300 V / 6.3 A / #22...10 AWG	300 V / 6.3 A / #22...10 AWG
	VDE	400 V / 6.3 A / 2.5 m ²	400 V / 6.3 A / 2.5 m ²
Torque	Nm (lb. in.)	0.4...0.8 (3.5...7.0)	
Clamping screw	M	2.5	3
Selected Accessory Data*			
End Plate (AP) (thickness mm)		Type	Part No.
	Beige Wemid	WAP (2.5-10)	1050000000
	Blue Wemid	WAP (2.5-10 BL)	1050080000
	Beige Wemid	WTW (2.5-10)	1050100000
	Blue Wemid		
Jumpers			
	2 pole	QL 2	0215800000
	3 pole	QL 3	0215900000
	4 pole	QL 4	0216000000
	10 pole	QL10	0338000000
	24 pole	WQB 24/16	1579060000
	41 pole		
	Blank		
	Black		
	Blue		
	Red		
	Jumper screw	BS M 3x5	1052100000
Test Plug/Socket			
	Test plug		PS 2.3
	Test adapter		WTA 6
G Fuse Cartridges, 5 x 20 mm			
Rated current (A):	0.10 rapid-blow	0430300000	0430300000
Rated voltage 250 VAC	0.20 rapid-blow	0430400000	0430400000
Note: For listing of 5 x 25 mm fuses see page 28.	0.25 rapid-blow	0430500000	0430500000
	0.50 rapid-blow	0430600000	0430600000
	1.0 rapid-blow	0430700000	0430700000
	1.6 rapid-blow	0430800000	0430800000
	2.0 rapid-blow	0430900000	0430900000
	2.5 rapid-blow	0431000000	0431000000
	3.15 rapid-blow	0431100000	0431100000
	4.0 rapid-blow	0431200000	0431200000
	5.0 rapid-blow	0431300000	0431300000
	6.3 rapid-blow	0431400000	0431400000
Tools			
	Notching tool for QL jumper hole	WAW 2	0900450000
Marking Tags			
	Consecutive horizontal	DEK 5/5	0473460001
	Consecutive vertical	DEK 5/5	0473560001
	Blank		WS 12/6
	Printed		WS 12/6

Note: Part numbers shown are for a single card of pre-printed tags numbered 1-50. For additional information, see Accessories section.

RAIL MOUNTED TERMINAL BLOCKS: W-SERIES