




Disconnect Terminals

WTR 4

new WDTR 2.5

WDTR 2.5/WE



Lever

Dual Lever

Branch

Terminal Block Selection Data

Available Options	Version	Part No.	Part No.	Part No.
	Beige Wemid	7910180000		9528090000
	Beige Wemid with StB 2.3	7910210000	(4) StB 2.3	9528070000
	Blue Wemid	7910190000		
	Blue Wemid with StB 2.3	7910220000	(4) StB 2.3	9528080000

Dimensions

Width / Length / Height mm (in.) for TS 35 x 7.5	6/60/47 (.24/2.36/1.85)	6.2/94/69 (.25/3.7/2.72)	6.2/89/69 (.125/3.19/2.72)
Insulation stripping length mm (in.)	13 (.51)	8 (.31)	8 (.31)
Screwdriver blade (for test sockets)			3.5 x 0.6

Technical Data

Rated voltage / rated current / wire size	UL	300 V / 30 A / #22...10 AWG*	300 V / 10 A / #22...12 AWG	300 V / 10 A / #22...12 AWG
	CSA	600 V / 22 A / #22...10 AWG	300 V / 10 A / #26...12 AWG	300 V / 10 A / #26...12 AWG
	VDE	400 V / 24 A / 4 mm²	400 V / 13 A / 2.5 mm²	400 V / 10 A*** / 2.5 mm²
Torque Nm (lb. in.)				0.5 (4.4)
Clamping screw	M			M3


Selected Accessory Data†

End Plate (WAP) / Partition (WTW) (thickness mm)	Type	Part No.	Type	Part No.	Type	Part No.
 Beige Wemid	WAP (1.5)	1050000000	Not Required			
 Beige Wemid	WTW (3)	1050100000	Not Required		WTW (3)	1050100000
 Blue Wemid	WAP (1.5)	1050080000	Not Required			

Jumpers

 2 pole	ZQV 4N/2	1758250000				
 3 pole	ZQV 4N/3	1762630000				
 4 pole	ZQV 4N/4	1762620000				
 10 pole	ZQV 4N/10	1758260000				
 41 pole	ZQV 4N/41	1758270000				
 Blank	QB 75/6.2/15	0535200000				
 Black	ISPF QB75 SW	0526700000	VQB1.5/50BLK	1635120000	VQB1.5/50BLK	1635120000
 Blue	ISPF QB75 BL	0526780000	VQB1.5/50BL	1633280000	VQB1.5/50BL	1633280000
 Red	ISPF QB75 RT	0526760000	VQB1.5/50RT	1633290000	VQB1.5/50RT	1633290000

Test Plugs / Sockets

 PS 2.3	PS 2.3	0180400000	PS 2.3 (ø 2.3)	0180400000	PS 2.3 (ø 2.3) for #14 AWG wire	0180400000
 Test adapter	WTA 6	1632380000				

Tools

 Screwdriver	SDIK for StB test socket/screw	9024930000	SDIK for StB	9024930000	SDIK for StB test socket/screw	9024930000
---	--------------------------------	------------	--------------	------------	--------------------------------	------------

Diode Plugs

 - +				WSD 2.5	1058460000
+ -				WSD 2.5	1058560000
With wire link				WSD 2.5	1058660000
Plug enclosure only				WSD 2.5	1058760000

Fuse Plugs

	for 5x20 SIHA	without LED	with LED		
SIHA 2/G 20	400 V	9537600000			
SIHA 2/G 20	10-36 AC/DC		9537610000		
SIHA 2/G 20	35-70 AC/DC		9537620000		
SIHA 2/G 20	60-150 AC/DC		9537630000		
SIHA 2/G 20	160-250 AC/DC		9537640000		
	.56-2.30 mm leakage current				

Marking Tags

	Consecutive horizontal	DEK 6	4686600000	DEK 5/6	0468660001	FW 6.5	0468160001
	Consecutive vertical	DEK 6	4687600000	DEK 5/6	0468760001	FW 6.5	0468260001
	Blank	WS 12/6	1609900000				
	Printed	WS 12/6	1447660000				

*Pending

***Rated current to 1 A when using the diode plug with soldered diode.

Diode plug can only be used in place of upper level disconnect switch.

†See Accessories section for additional information.