




Pluggable Terminals



WDU 1.5/BLZ 5.08




WDU 1.5/BLZ/R 5.08




WDU 1.5/BLZ/LD 5.08

with LED red



WDU 2.5/BLZ R 7.62



Terminal Block Selection Data

Available Options	Version	Part No.	Part No.	Part No.	Part No.
	Beige Wemid	1577340000			1038900000
	Blue Wemid	1596900000	1577390000		
	with LED red			12 V	1577350000
	with LED red			24 V	1577360000
	with LED red			48 V	1577370000
	with LED red				
Dimensions					
Width / Length / Height mm (in.)	for TS 35 x 7.5	5/57.5*/55.5* (207/2.26/2.18)	5 / 45.4/57.5* / 45/55.5*	5 / 45.4/57.5* / 45.0/55.5*	7.62 / 45.4 / 57.5* / 45.0 / 55.5
Insulation stripping length	mm (in.)	10 (.39)	10 (.39)	10 (.39)	10 (.39)
Technical Data					
Rated voltage / rated current / wire size	UL	300 V / 10 A / #22...12 AWG	300 V / 20 A / #26...16 AWG	300 V / 20 A / #22...12 AWG	-
	CSA	300 V / 10 A / #26...12 AWG	- / - / #26...12 AWG	- / - / #26...12 AWG	-
	VDE	250 V / 10 (2x8) A / 1.5 mm ²	1.5 mm ²	1.5 mm ²	
Torque	Nm (lb. in.)	0.5 (4.5)	0.5 (4.5)	0.5 (4.5)	0.4...0.6 (3.5...5.25)
Clamping screw	M	2.5	2.5	2.5	

Selected Accessory Data*

End Plate (WAP, AP) / Mounting Bracket (WBB)**	Type	Part No.	Type	Part No.	Type	Part No.	Type	Part No.
WAP (thickness 2.5 mm)	With pin***	1577320000	With pin	1577320000	With pin	1577320000	With pin	1577320000
	Without pin††	1577330000	Without pin	1577330000	Without pin	1577330000	Without pin	1577330000
WBB orange (thickness 5 mm)	With pin	1068260000	With pin	1068260000	With pin	1068260000	With pin	1073600000
	Without pin	1068160000	Without pin	1068160000	Without pin	1068160000	Without pin	1073500000
Jumpers								
Note: Final number in model indicates no. of poles (e.g. WQV 2.5/2 = 2 poles). For more information, see Accessories section.								
	WQV 2.5/2	1053660000	WQV 2.5/2	1053660000	WQV 2.5/2	1053660000		
	WQV 2.5/3	1053760000	WQV 2.5/3	1053760000	WQV 2.5/3	1053760000		
	WQV 2.5/4	1053860000	WQV 2.5/4	1053860000	WQV 2.5/4	1053860000		
	WQV 2.5/5	1053960000	WQV 2.5/10	1054460000	WQV 2.5/10	1054460000		
	WQV 2.5/6	1054060000						
	WQV 2.5/7	1054160000						
	WQV 2.5/8	1054260000						
	WQV 2.5/9	1054360000						
	WQV 2.5/10	1054460000						

Tools						
Cutting tool WAW 1 for WQV	WAW 1	9004500000	WAW 1	9004500000	WAW 1	9004500000
Screwdriver	SD	9008330000				

Negative conductor-busbar					
0.5 x 4 x 120 mm		ML-SSch	1063200000	ML-SSch	1063200000

Cover for Unused Pins						
	WAD 5/2	1577400000	WAD 5/2	1577400000	WAD 5/2	1577400000

Coding Keys					
	Note: Coding keys allow for specific mating of plugs to terminal.	BLZ-KO	1545710000	BLZ-KO	1545710000

Plugs		No. of positions				
(For additional plug positions, refer to Printed Circuit Board Products Catalog, LIT0110).	BLZ 5.08	4	BLZ 4	1526660000	BLZ 4	1526660000
		6	BLZ 6	1526860000	BLZ 6	1526860000
		8	BLZ 8	1527060000	BLZ 8	1527060000
	BLZ 5.08	4	BLZ 4 B	1528960000	BLZ 4 B	1528960000
	with lateral dovetail guide	6	BLZ 6 B	1529160000	BLZ 6 B	1529160000
		8	BLZ 8 B	1529360000	BLZ 8 B	1529360000
	Locking blocks		BB 12	1593450000	BB 12 R	1593450000

Marking Tags		Print				
Note: Part numbers shown are for a single card of pre-printed tags numbered 1-50.		Consecutive horizontal	DEK 5/5	0473460001	DEK 5/5	0473460001
For additional information, see Accessories section.		Consecutive vertical	DEK 5/5	0473560001	DEK 5/5	0473560001

* With BLZ

** Bracket for attaching plug to the terminal block requires use of locking block (BB) mounted on plug.

*** With pin mounts to closed side of terminal.

† See Accessories section for additional information.

†† Without pin mounts to open side of terminal.