



General ordering data

Order No.	8708730000
Short text for material	CP SNT3 1000W 24V 40A
EAN	4032248380893
Qty	1

Input

Input voltage	3x400 V AC / 340...575 V AC (450...800 V DC)
Input current	3.4 A @ 400 V AC
Making current limit	< 70 A (bei 25 °C)
Input frequency	47...63 Hz
Overvoltage protection	Varistor
Input fuse	External via 3 circuit-breakers up to 10...16 A, char. C

Output

Connection system	Screw connection
Output voltage	24...28 V DC (adjustable via potentiometer)
Output current	40 A
Control at 10...100% load	< 2 %
max. residual ripple	< 100 mVss / bandwidth 20 MHz
Overload protection	105%...130% Ikonst of max. output power, automatic restart
Status relay / Change-over contact	250 V AC (max. 30 V DC) / 1 A
max. output power	960 V
Parallel connection option	direct for same type

General data

Status indication	green LED
Installation advice	Clearance: above/below ≥ 3 cm
EMC standards	EN 55011, EN 55022, EN 55024, EN 61000-6-2, 3
Weight	3,5 kg
Standards	EN 60204 (PELV)
Degree of efficiency at max. load	88 %
Mounting position horizontal	on mounting rail TS 35
Operating temperature	-10 °C...+55 °C
Storage temperature	-20 °C...+85 °C

Insulation coordination

Electrical isolation, output-earth	0.5 kV AC
Electrical isolation, input-earth	1.5 kV AC
Electrical isolation, input-output	3 kV AC

Dimensions

Clamping range, max.	6 mm ²
Clamping range, nom.	4 mm ²
Clamping range, min.	0,13
Length	125 mm
Height	150 mm
Width	280 mm

Approvals

Approvals	CE / cULus 508 / cULus 60950
-----------	------------------------------

Classifications

ETIM 2.0	EC001039
ETIM 3.0	EC001039
eClass 4.1	27-24-04-10
eClass 5.0	27-24-22-13
eClass 5.1	27-24-22-13

Related products

Order No.	Short text for material
8708700000	CP SNT3 250W 24V 10A
8708710000	CP SNT3 500W 24V 20A