



General ordering data

Order No.	8710620000
Short text for material	CP DM 10
EAN	4032248385706
Qty	1

Input

Input voltage	40 V DC max.
Input current	2 x 0...10 A max.

Output

max. output power	480 W
Connection system	Screw connection
Output voltage	Vin - 0,5 typ
Output current	0...20 A max. oder 10 A max. bei Redundanzbetrieb

General data

Installation advice	Clearance: side \geq 2 cm; above/below \geq 10 cm
Weight	0,15 g
Degree of efficiency at max. load	96 %
Mounting position horizontal	horizontal
DIN Rail compatibility	Tragschiene TS35 nach DIN 50022
Operating temperature	-10 °C...+55 °C
Storage temperature	-20 °C...+85 °C

Dimensions

Clamping range, min.	0,21 mm ²
Clamping range, nom.	4 mm ²
Clamping range, max.	4 mm ²
Length	110 mm
Height	125 mm
Width	55,5 mm

Approvals

Approvals	CE / cULus 508 / cULus 60950
-----------	------------------------------

Classifications

ETIM 2.0	EC001039
ETIM 3.0	EC001039
eClass 4.1	27-24-04-10
eClass 5.0	27-24-22-13
eClass 5.1	27-24-22-13

Related products

Order No.	Short text for material
8768650000	CP DM 20