



### General ordering data

Order No.	9919372415
Short text for material	CP DCDC 50W 15V 3A
EAN	4032248217847
Qty	1

### Input

Input fuse	internal
max. connection range	AWG26-12 (0.1-4.0 mm <sup>2</sup> )
Input voltage	18...30 V DC, typ. 24 V DC
Connection system	Screw connection

### Output

Connection system	Screw connection
Output voltage	15 V DC
Output current	3 A
max. connection range	AWG26-12 (0.1-4.0 mm <sup>2</sup> )
Overload protection	Overcurrent cut-out with self-reset
Overload behaviour	Overvoltage cut-out with self-reset
max. output power	45 V

### General data

Weight	417 g
Standards	EN 50178, EN 60950, IEC950
Switching frequency	200 kHz
Low Voltage Directive	73/ 23/ EWG
Status indication	green LED
EMC standards	IEC 61000-6 /-2
Enclosure	Metal
DIN Rail compatibility	TS 35
Operating temperature	0 °C...+40 °C max. full rate load
Storage temperature	-40 °C...+85 °C

### Insulation coordination

Humidity at storage temperature	20 to 90% RH without condensation
Humidity at operating temperature	20 - 85% RH
Ingress protection class	IP 20

**Dimensions**

Clamping range, min.	0,1 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>
Clamping range, nom.	4 mm <sup>2</sup>
Length	131 mm
Height	98 mm
Width	57 mm

**Approvals**

Approvals	CSA;ULUR;CE;
-----------	--------------

**Classifications**

ETIM 2.0	EC001039
ETIM 3.0	EC001039
eClass 4.1	27-24-04-10
eClass 5.0	27-24-22-13
eClass 5.1	27-24-22-13

**Related products**

Order No.	Short text for material
9919372424	CP DCDC 50W 22-24V 2A
9919371212	CP DCDC 50W 12V 3A
9919371205	CP DCDC 50W 5V 8A
9919371224	CP DCDC 50W 22-24V 2A
9919371215	CP DCDC 50W 15V 3A
9919372412	CP DCDC 50W 12V 3A
9919372405	CP DCDC 50W 5V 8A